
S-50 Computing

for 6800 and 6809 users



6809 DISK SYSTEMS

All disk systems are supplied with our version of FLEX 9, the world standard disk operating system for the 6809. Our systems normally operate in double density format, but they are compatible with single density, or single sided recording formats. FLEX is supplied with over forty utilities, many of which are only available with our systems.

Our disk systems offer you mass storage at low cost. The cost per thousand bytes of storage for our various systems is shown in the chart. Other 6809 disk systems have costs up to three times greater for the same general type drive.

D-5 Two double sided, double density, 5" disk drives with a total on
line capacity of 720,000 bytes of data. Includes cabinet, power supply,
connecting cable and controller. Controller will operate up to four
drives. This is an ideal disk system for small stand alone word proces-
sing systems, or for businesses that do not work with large inventories.

14 x 6 x 10 - 20 lbs		\$1,295.00
----------------------	--	------------

DT-5 Double track density version of the D-5. The DT-5 uses two 96 track per inch drives to provide an on line capacity of 1,400,000 bytes. Includes cabinet, power supply, connecting cable and controller. Controller will operate up to four drives. This is a disk system with enough capacity to include small inventories of up to 1,000 items, plus the usual business package of general ledger payroll, etc.


14 x 6 x 10 -	- 20 lbs	\$1,695,00

DMF-2 Double sided, double density, dual eight-inch disk system with an on line capacity of 2,400,000 bytes. Our "top of the line" disk system features a DMA type controller for fastest possible data transfers. This drive was designed for larger businesses and multi user installations. The DMF-2 will provide the fast operation necessary for systems running multiterminals under the UniFLEX operating system. Complete with a heavy duty 1/8-inch metal cabinet, power supply, connecting cable and controller. The controller will operate up to four drives.

$17\% \times 5 \times 21\% - 53 \text{ lbs} \dots \dots$	
--	--

CDS-1 This "Winchester" type hard disk provides both large storage capacity and high speed operation. The CDS-1 is the answer for systems that must handle large inventories or systems with more than four terminals. The controller has its own processor and uses DMA data transfer.

CDS-1 — 115 lbs	\$4,395.00
-----------------	------------







DMF2





SOUTHWEST TECHNICAL PRODUCTS CORPORATION 219 W. RHAPSODY SAN ANTONIO, TEXAS 78216 (512) 344-0241



The Di Systen 6809

FLEX™ is the most operating system microprocessors. I years, it has beco standard. FLEX is a mount of 6800/c being marketed. now available an editor and assem

FLEX for the EXO

Runs on a Motoro EXORdisk™ II or III. modifications with of memory re-adc boot as MDOS™.

FLEX for General

Fully documented write his own term routines to adapt Three system requileast 12K of RAM c at \$A000 for 6800 c floppy disk drive c soft sectors. This po beginners!



The Disk Operating System For 6800 and 6800 Users

FLEX™ is the most widely used disk operating system for the 6800 and 6809 microprocessors. Field proven for over two years, it has become an industry standard. FLEX is unparalled in the amount of 6800/6809 support software being marketed. Two new versions are now available and each includes a disk editor and assembler:

FLEX for the EXORciser™

\$450.00

Runs on a Motorola EXORciser with EXORdisk™ II or III. Requires no hardware modifications with the possible exception of memory re-addressing. Uses the same boot as MDOS™.

FLEX for General Use

\$150.

Fully documented to allow a user to write his own terminal and disk I/O routines to adapt to most any hardware. Three system requirements are: (1) at least 12K of RAM at \$0000; (2) 8K of RAM at \$A000 for 6800 or \$C000 for 6809; (3) floppy disk drive capable of 256-byte, soff sectors. This package is not for beginners!

FLEX Support Software

Extended BASIC Standard BASIC	\$100.00 75.00
Diagnostics Package	75.00
Text Processing System	75.00
Sort/Merge	75.00
6809 Cross Assembler	100.00
6809 FLEX Utilities	75.00
6800 FLEX Utilities	100.00
Debug Package	75.00
FLEX for SWTPc	150.00

Be sure to specify disk size and 6800 or 6809. All orders should include 3% postage and handling (10% on foreign orders). Mastercharge and Visa are welcomed. Write for a complete software catalog.



Box 2570, West Lafayette, IN 47906 (317) 463-2502 Telex 276143

FLEX is a trademark of Technical Systems Consultants, Inc. EXORciser, EXORdisk, and MDOS are trademarks of Motorola, Inc.

Big Savings for SS-50 Bus Computerists

\$140!

LFD-400'Mini-Disk System

\$459.95

The choice of knowledgeable 680X computerists since 1977 ● Proven clock-data separation circuitry and other superior design features ● Reliable hard-sector diskette formatting ● Stores up to 102 Kbytes of formatted data on 40 tracks • Comes complete with 4-drive controller, drive assembly, 6800 or 6809 ROM disk operating system, interconnecting cable and comprehensive users manual • Add-on drives cost only \$399.95

REGULAR \$599.95

SBC/9'Single-Board Computer

\$139.95

A computer or a fully compatible SS-50 bus MPU card ● Interchangeable 6802 or 6809 processor • Extendable 1-Kbyte ROM monitor • Parallel and 1-Notive ROM monition ● Parallel and serial I/O ports — selectable, full-range bit rate generator for serial I/O ● Extendable addressing ● On-card 1-Kbyte RAM ● Provision for additional EPROM ● On-card voltage regulator circuits

REGULAR \$199.95

Save

\$60!

6809 MPU Upgrade Adapter **\$39.95**

Upgrades 6800 MPU cards to 6809 processing power © Configured for SWTP MP-A2 MPU card but may be used with other MPUs ● Plug-in installation requires no trace

MPUs • Prug-in installation requires no trace cutting or soldering — easy to restore MPU to original configuration • Assembled and tested • Includes user instructions • 6809 ROM operating system, PSYMON/A2, for use with the 6809 MPU Adapter —

Save \$30!

REGULAR \$69.95

The ELECTRIC WINDOW

\$169.95

Memory-mapped instant display updating
Software-defined display formats
Expandable 128-symbol character generator — characters are fully formed and feature true baseline descenders • On-card display RAM can be remapped Video output can be composite or separate sync-video • Voltage regulation circuitry included on card. For an application review of the ELECTRIC WINDOW, see Peter Stark's comments on page 87 of the January 1981 issue of Kilobaud/ MICROCOMPUTING.

REGULAR \$249.95



Save \$80!

Percom Price-Slashing, Profit-Zapping Fifth Anniversary Sale

After five years of solid accomplishments, it's time to celebrate. So we've slashed prices for a gigantic 5th anniversary sale. Now, for a limited time, you can get Percom design and Percom quality at enormous savings. But don't wait. Sale ends May 30th and quantities are limited to stock on hand.

Save \$100.00 on fully assembled, tested and burned-in RAM cards! Hurry, regular prices in effect after April 30th.

These RAM cards feature 1-Mbyte extended addressing; buffered data, address and control lines; and, on-card voltage regulation. Cards are fully tested and burned-in. User manuals include 6800 & 6809 diagnostic memory test programs.

M24SS 24-Kbyte STATIC RAM CARD

\$399.95 REGULAR \$499.95

Save \$100!

Memory is organized as three independent 8-Kbyte blocks. Each block may be located at any 8-Kbyte boundary of a 64-Kbyte address space Also available in 8- and 16-Kbyte versions at regular prices, 8-Kbyte RAM expansion kit includes extra RAM chip, plus sockets and other parts. Kit price is \$139.95. ● Uses 2114L RAM chip.

M48DSS 16-Kbyte DYNAMIC RAM CARD

\$399.95

REGULAR \$499.95

Save

Expandable to 48 Kbytes Memory is organized as three \$100!

independent 16-Kbyte blocks. Each block may be located in any of the four 16-Kbyte zones of a 64-Kbyte address space Special "map-out" strapping can be used to depose any 8-Kbyte block from upper 32-Kbyte memory ● Uses type 4116 RAM chips ● 16-Kbyte RAM expansion kit includes extra RAM chip, plus sockets and other parts. Kit price is \$99.95.

Watch for the COLORAMA-50'!

This soon-to-be-announced color VDG card for the SS-50 bus features eleven colorful display formats in 2 to 8 colors, plus 2-color alphanumerics; full graphic resolutions from 64X64 pixels to 256X192 pixels; memory-mapped instant display control; low-cost modulator option for TV interface; 1-Mbyte extended addressing; cassette I/O option; and, operating software. Introductory price is only \$219.95.



PERCOM DATA COMPANY, INC. 211 N KIRBY GARLAND, TEXAS 75042 (214) 272-3421

PRICES AND SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

PRICES DO NOT INCLUDE SHIPPING AND HANDLING.

Nobody supports the SS-50 bus like Percom

Our field-proven software for 680X computers includes monitors, operating systems, drivers, editors, assemblers, debuggers and high-level languages like Super BASIC — our popular extended disk BASIC interpreter.

Some of the other hardware products available include versatile protosome of the other hardware products available include versatile proto-typing cards in both 30- and 50-pin versions, extendable 50-pin motherboards and 30-pin I/O card motherboards. Function cards, prototyping cards and motherboards are optionally available with gold-plated bus connectors. Also, most function cards are available in 86-pin, EXORciser bus compatible versions.

Quality Percom products are available at Percom dealers nation-wide. Call toll-free, 1-800-527-1592, for the address of your nearest dealer, or to order direct from Percom.

SMOKE !

3 Powerful

DCB-4 Disk Master Double Density Contro and DOS68D Double De \$449.00

The new DCB-4 is a truly state-of ment which allows up to 366K by on a single 51/4" disk and has th

- Up to four 51/4" and four 8 handled in the same system finable logical unit table. (E compatible with future hard d
- Under software control, the the following for any drive:
 - Single sided or double sided ☆ Single density or double de
 - ☆ 5¼" or 8".
 - ☆ Stepping Rate.

 - 40 track or 35 track dea sided 5¼" drives.
 - ☆ User can select the system ration.
- Occupies only 16 bytes of (F760-F76F standard). User s 16 byte address space.
- Can read and write a single On-board buffer memory al rupt capability in interrupt Once data transfer has bee more processor time is require
- Contains extended decoding tended addressing per SS-! can be enabled by an option ju
- SSB provides a means for c written by older versions o read by DOS68D. All new r by DOS68D can be read by a of DOS68. DOS68 is SSB's 6 ting system.
- Track Ø of side Ø is recorde sity per IBM standard.
- Phase-locked-loop assures his grity attainable.

All of these features are available delivery on one standard 51/2" x 9" SS-50C card for only \$449.00. The DOS68D version 5.1, MONITOR diskette, and a manual with the sou



31336

COLORAMA-50, ELECTRIC WINDOW, LFD-400, PSYMON and SBC/9 are trademarks of Percom Data Company, Inc.

EXORciser is a trademark of Motorola Corporation.

SMOKE SIGNAL BROADCASTING

Presents

3 Powerful New SS-50/SS-50C Boards

DCB-4 Disk Master Double Density Controller Board and DOS68D Double Density DOS \$449.00

The new DCB-4 is a truly state-of-the-art development which allows up to 366K bytes to be stored on a single 5%" disk and has these outstanding features:

- Up to four 5¼"and four 8" drives can be handled in the same system with a user definable logical unit table. (DOS68D will be compatible with future hard disk systems).
- Under software control, the user can select the following for any drive:
 - ☆ Single sided or double sided operation.
 - ☆ Single density or double density data.
 - ☆ 5¼" or 8".
 - ☆ Stepping Rate.
 - ☆ 40 track or 35 track density on double sided 5¼" drives.
 - User can select the system boot configuration.
- Occupies only 16 bytes of memory space (F760-F76F standard). User selectable to any 16 byte address space.
- Can read and write a single sector by itself.
 On-board buffer memory allows full interrupt capability in interrupt driven systems.
 Once data transfer has been initiated, no more processor time is required.
- Contains extended decoding circuitry for extended addressing per SS-50C bus which can be enabled by an option jumper.
- SSB provides a means for copying software written by older versions of DOS68 to be read by DOS68D. All new media formatted by DOS68D can be read by all older versions of DOS68. DOS68 is SSB's 6800 disk operating system.
- Track Ø of side Ø is recorded in single density per IBM standard.
- Phase-locked-loop assures highest data integrity attainable.

All of these features are available for immediate delivery on one standard $5\frac{1}{2}$ " x 9" 50 pin SS-50/SS-50C card for only \$449.00. The price includes DOS68D version 5.1, MONITOR object code on diskette, and a manual with the source listing.

SCB-69 Super Computer Board 6809CPU Board \$299.00

The most versatile 6809 CPU Board on the market is now available from Smoke Signal Broadcasting and has the following features:

- Standard 2 MHz operation.

 (Shipping 1 F MHz until August 6)
- (Shipping 1.5 MHz until August 80)
- 20 bit address generation for up to 1 Mbyte of memory. Uses an improved address translation RAM which is compatible with present extended addressing schemes yet requires much less overhead when used in multi-user systems.
- All on-board devices can be switch selected to occupy any or all extended pages. Any on-board device may be disabled and its memory space is then available for external memory.
- Standard real—time clock (time of—day, day—of—week, day—of month) with battery back up capable of generating programmable interrupts.
- Up to 20K of EPROM can be installed on the CPU Board.
- Standard 1K of RAM on board.
- Includes improved 6809 Monitor (and source listing).
- Contains an FPLA for decoding EPROM address and optional devices. Switches are used to select 2K/4K EPROM and Fast/Slow I/O.
- Contains provision for optional 9511/9512 floating point processor.
- NMI line is user selectable to work with either SS-50 or SS-50C busses.

Price for the new SCB-69 is only \$299.00 for an assembled, burned-in fully tested board.

M-32-X 32K Memory Board \$539.00 \$439.00

The first and only 32K Static Ram Board on standard size (5½" x 9") SS-50/SS-50C Bus Circuit Card is made by Smoke Signal.

- Switch selectable to any 4K boundary.
- Any 4K block may be switch enabled or disabled.
- Fully compatible with SS-50C extended addressing (allows memory decoding up to 1 Mbyte).
- Extended addressing capability may be switched off for compatibility with SS-50 systems.
- Gold Bus Connectors for high reliability.
- Guaranteed 2MHz operation (tested at 2.2 MHz).
- Low power consumption 8 volts at 2.4 amps typical.

M-32-X 32K Memory Board is priced at \$539.00.

M-24-X 24K Memory Board expandable to 32K, is \$439.00.

And our M-16-X 16K board is back to the old price of \$299.00.

SMOKE SIGNAL



BROADCASTING

31336 Via Colinas, Westlake Village, CA 91361, (213) 889-9340



m

Publisher/Editor Ken Orme

Assistant Publisher/Editor Robert Wood

> Review Editor Gary Manning

Office Manager Typesetting/Camera Bonnie J. Orme

Copyright © 1981
by SS-50 Computing
ALL RIGHTS RESERVED
Material in this publication
may not be reproduced
in any manner
without prior permission
in writing.

SS-50 Computing 133 North Mayfield Ave. Garland, Utah 84312

Send Correspondence To:

SS-50 Computing P.O. Box 398 Garland, Utah 84312 Phone [801] 257-5733

Subscription Rates:

1 Year [6 Issues] - \$12.00 2 Years [12 Issues] - \$22.00

Canada/Mexico - \$14.00 per Year All other countries - \$25.00 per Year [Airmail only] [U.S. Funds drawn on U.S. Banks] COVER PHOTO - A European 6800 CPU card...the "Newbear 77-68" taken by Peter Bendall. See article on p. 17

Contents

Mar-April / May-June Vol.2 - No. 2

EDITORIAL5
FEATURES AND REVIEWS
OS-9 Operating System6
West Coast Computer Faire 11
SS-50 - The 6800 in Europe 17
The Hitachi MB-689020
Boaz 64K Dynamic Update26
HARDWARE
FLEX AND OS-9 on SWTPC 6809 . 22
SOFTWARE
BASIC Bug
Open Door Patch Revisited15
LETTERS19
NEW PRODUCTS27
PERIPHERAL NEWSLETTER 30

Manuscripts submitted for publication should include sufficent return postage if needed to be returned. All materials should be original with full ownership rights by the said author. Programs submitted remain property of the author, with the exception that SS-50 Computing reserves the right to reprint the material in future publications.



by Ken

As you have pr cover date says Ma instead of March-A_l that even though w it is still impossibl when the post office days to get the mag

Even though we and articles put in a the delay in the magazine to have than we would like you will still get (even though it wo twelve) and we wil you don't miss out not change the expi your label. I kno continued support a have two issues wit on them to make They will most like and October issue with the Novemb back to the bi-mont

Things are look a lot of help and su you with articles a want to thank you I'm sure that we make SS-50 Comp that you would like

Despite the po foreign and domes news in that we w subscription price of We intend to continuas we can physical no one here at S dependent on this



Editorial

by Ken Orme

As you have probably noticed, our cover date says March-April/May-June instead of March-April. Well, it seems that even though we are getting better, it is still impossible to get caught up when the post office takes from 30 to 40 days to get the magazine to you.

Even though we are able to get ads and articles put in at the "last minute" the delay in the mail causes the magazine to have an older cover date than we would like to see. Never fear, you will still get six issues per year (even though it would be nice to have twelve) and we will keep track so that you don't miss out even though we will not change the expiration date listed on your label. I know that with your continued support and patience, we will have two issues with a single cover date on them to make up for the change. They will most likely be the September and October issues that are separate with the November/December issue back to the bi-monthly date.

Things are looking quite well, with a lot of help and support from many of you with articles and information. I want to thank you for the support and I'm sure that we can continue to make SS-50 Computing the magazine that you would like it to be.

Despite the postal increase (both foreign and domestic), we have good news in that we will not increase the subscription price of SS-50 Computing. We intend to continue this price as long as we can physically do so. After all, no one here at SS-50 Computing is dependent on this publication for our

living, so we are willing to keep prices down as long as possible. After all, we started a bit high with the knowledge that postal increases would come.

One of the things that we have to change is that there will not be a surface rate for foreign subscriptions. The reason for this is that it takes too long to pull the surface magazines from the pile, since about 98 percent of them are airmail. We are trying to hold down the costs on the foreign subscriptions as well, but will probably have to increase them next year by a dollar per year. The difference in what it costs for a U.S. subscription and a foreign one is all in postage.

I suppose that there will come a time when we will be able to get out a monthly publication, but unless we just copy letters and articles the way they come to us we won't be able to do it this year. If we could spend all of our time doing this publication, we would easily accomplish that goal. But, as we have told you in other issues, we do this part-time and therefore cannot spend all day on it (in addition to all night, quite often).

BACK ISSUES

Many new subscribers have joined ranks with you that have been with us from the beginning, so I must say once again that there are a few back issues available, but two of the issues are completely sold out. Issue #1 is gone and so is issue #3. The other ones (#2, #4, and #5) are available for \$3.00 each and #6 & #7 are \$2.50 each. We receive several letters a day asking about back issues, so this should help to clarify the current situation.

Keep those letters and articles coming in...After all, we want to have you share with others, too!

[SS-50]

OS-9 REVIEW

A MODULAR OPERATING SYSTEM

by Ken Orme

OS-9 from Microware is a versatile multi-programming operating system for the 6809. It manages memory, I/O, and CPU time for efficient operation and is a powerful interface that is easy to learn and use. It features device independent unified I/O that is expandable.

This operating system is a result of developing the BASIC09 Advanced Programming Language development by Microware and Motorola between 1978 and 1980. The design is modeled somewhat after Bell Telephone Labor-'UNIX' operating system. Microware explains that a "clone" of UNIX for the 6809 would be easy to implement, but since UNIX was designed for fairly large-scale minicomputers (such as the PDP-11), it is expected to have high CPU throughout, large and fast disk storage devices and a static I/O environment. Also, it is not particularly time or disk-storage efficient when used with low-cost disk drives.

OS-9 retains the overall concept and user interface of UNIX, but rather than

dynamically swapping programs on and off the disk, it keeps running programs in memory and emphasizes efficient use of available RAM. Also, it supports re-entrant software that can be shared by several users simultaneously which reduces overall memory requirements. It does have "Fork" and "Execute" calls that have been improved over the UNIX equivalents.

It effectively handles modular ROMed software by using the "Memory module" and LINK features to permit ROMed software to be automoatically identified, linked, shared, updated and repaired.

The nice thing about OS-9 is the fact that it is modular. That means for the small systems, just 2 or 3K or RAM would be needed in addition to the 6809 CPU and 4K of ROM. A large system could consist of several disk systems (including hard disks), multiple terminals and 256K (or more) or RAM with memory management hardware (the Level Two OS-9 system). Level Two will handle up to one megabyte of memory.

The heart of the to as the "Kernal" administrator, supe manager of the C about 3K long and ROM at the highest

It handles ment MPU management ing), interrupt prequest processing, ization after restarequests" are call Real-time function slicing, time-keep service are autoroutinely during system.

The input/outp mentioned since t directly process the instead is separ allowing OS-9 to different hardware I/O service reques subsystem called the for I/O manager).

Memory manag ant part of the oper allocates RAM mer which makes it eff: unique. Both the AND the logical co managed with a names, addresses "memory modules aged much like a though it is RAl advantages to this run-time "linking libraries of utility "sharing" of re-en replacement of sm programs for updat when in ROM).

The OS-9 symultiprogramming which allows syprograms (processes simultaneously. Friate service requesource may be process. In order gramming capability

The heart of the system is referred to as the "Kernal", of which is the administrator, supervisor, and resource manager of the OS-9 system. It is about 3K long and normally resides in ROM at the highest memory addresses.

It handles memory management, MPU management (for multiprogramming), interrupt processing, service request processing, and system initialization after restart. The "service requests" are calls from programs. Real-time functions such as timeslicing, time-keeping, and interrupt service are automatic and occur routinely during operation of the system.

The input/output functions are not mentioned since the Kernal does not directly process them. The I/O system instead is separate and modular, allowing OS-9 to be used with many different hardware configurations. The I/O service requests are passed to a subsystem called the "IOMAN", (short for I/O manager).

Memory management is an important part of the operating system. OS-9 allocates RAM memory as it is needed, which makes it efficient and somewhat unique. Both the physical assignment AND the logical contents of memory is managed with a directory of module names, addresses, and sizes using "memory modules". There are managed much like a disk system, even though it is RAM memory. Some advantages to this include automatic run-time "linking" of programs to libraries of utility modules, automatic "sharing" of re-entrant programs, and replacement of small sections of large programs for update or correction (even when in ROMI.

The OS-9 system is a true multiprogramming operating system, which allows several independent programs (processes) to be executed simultaneously. By using the appropriate service requests, any system resource may be accessed by the process. In order to use the multiprogramming capability, a hardware real-

time clock must be used. This clock should generate interrupts at a regular rate of about 100 times per second. Since the Kernal processes interrupts, all FIRQ interrupts are vectored to the clock service routine and the SWI, SW12, and SW13 interrupts are vectored to user-definable addresses.

OUR REVIEW SYSTEM

The system we used to test and review the OS-9 Level One Operating System contains a 6809 CPU, 56K RAM memory, 6K of ROM (4K in the operating system and 2K for the disk system), and a dual minifloppy disk system.

After receiving OS-9, all of the staff began reading through the manuals before trying to bring it up. One of the things that we all noticed was the new set of terms to go along with OS-9. Not that it is bad, but you should realize that the terminology is as new as the way OS-9 operates. It does take a little time to get the jargon down and to understand what to do to get a task accomplished.

To install OS-9 you must be aware that it doesn't use a "monitor ROM" as such. The OS-9 ROM set (4K total) replaces the monitor. The "part one" ROM MUST be installed at \$F800 through \$FFFF and the other ROM (or ROM's) may be installed at any address. With our system (SWTPc 6809) and some others, there is a third disk driver ROM which also may be at any address. Since we had the Southwest Technical CPU card with three extra sockets for EPROMs or ROMs we used it. By the way, we added a switch which allows us to use either OS-9 or SBUG-E, depending on position. (See article in this issue.) Also, you should make sure the terminal, disk controller, and other I/O devices are installed according to the instructions for your system, and that the interrupt jumpers or switches are enabled.

SYSTEM STARTUP

The startup procedure is very simple. Turn the computer on...the master disk drive select light should come on, and then just insert the OS-9 system disk and close the door. It will load a couple of modules into memory and then display a startup message:

Shell

OS-9:

At this point, we had trouble the first time we tried to run, because we didn't get the startup message. Later, we found out that our memory was not addressed contiguosly, which is one of the things mentioned, as a "must" in the instructions. After correcting this problem, the system fired up just like it should.

As you can see from the startup message, the first thing that comes up is the "shell". The shell surrounds the kernal of a seed and so it seems reasonable that the "shell" program surrounds the "kernal" or core of OS-9. You most likely will be running the system console until you get OS-9 commands and features tried and tested. After that, additional terminals and operators may also operate the system after "logging-on". It requires a correct user number and password before you may talk to the Shell.

After the prompt is displayed, you may begin to enter commands to the Shell. The normal command line is a PROGRAM NAME with PARAMETERS added. The program name is usually typed with the path list, file name, or other parameter after it.

The command programs include:

ATTR - Sets file attributes

BACKUP - Make backup of disk

BUILD -Build a new text file

CHD - Change working

Data directory

CHX - Change working Execution directory

COBBLER - Build a new boot file COPY - Copy data from a path to another

DATE - Display system date

DEL - Delete a file

DIR - Display Names in Directory

Dump - Perform a File Dump

Echo - Echo Input line to Output EX - Execute Program

FORMAT - Format a new diskette FREE - Display free space on device

KILL - Abort a process

LIST - List contents of a text file

LOGIN - Log user into system

LOAD - Load modules into memory

MAKDIR - Make a new Directory file

MDIR - Display Module Directory MFREE - List free memory areas

OS0gen - Makes boot file from keyboard entries

PROCS - Display procedure & status

RENAME - Change file name SAVE - Copy Memory Module to

File
SETIME - Start and set system

clock setpr - Set Process priority

TMODE - Change Terminal mode

TSMON - Timesharing terminal monitor

UNLINK - Release Memory Module

VERIFY - Verify module's CRC and header

Even though some of the command programs are for disk system only, most of them will work with a tape system as well. Even though we didn't have time to review OS-9 designed for tape systems, we will try to do so in a future article.

The main feature that makes OS-9 different from most other systems is that when you copy or list a program, it may be re-directed to another "path"

very easily. As a want a listing to the need to type: List means list the prograthe name) and let printer. All I/O denames and may be our disk was con "Term" which is the "T1", "T2" etc. for "P" the (parallel) printer unit zero, an unit one.

OTHER F

All of the promay be typed in up or upper and lower flexability in proprocesses and perming There are several that are also availated These include A Assembler; BASICO active debugger; E Editor; and STYL - terocessor. We withese and other professues.

The TMODE prochange the terminanceded or desired defined, the Controprevious input lir program interrupt; redisplay the precontrol Q is to Control W will ten to the terminal, w resuming the output delete; and ESCAPE

Most OS-9 soft which makes the m memory. If a progra has already been load another user, you wi copy instead of loads of the program ar memory. OS-9 also many processes are module and deletes

very easily. As an example, if you want a listing to the printer, you only need to type: List Program /pl which means list the program (you need to put the name) and let it go to the serial printer. All I/O devices have unique names and may be user defined, but as our disk was configured we have: "Term" which is the console terminal, "T1", "T2" etc. for other terminals, "P" the (parallel) printer, "DO" disk drive unit zero, and "D1" disk drive unit one.

OTHER FEATURES

All of the programs and names may be typed in upper case, lower case or upper and lower case. This allows flexability in program names and processes and permits easier readability. There are several optional programs that are also available from Microware. These include ASM - Interactive Assembler; BASIC09; DEBUG - Interactive debugger; EDIT - Macro Test Editor; and STYL - the Stylograph Word Processor. We will have reviews of these and other programs in upcoming issues.

The TMODE program allows you to change the terminal control keys as needed or desired. As originally defined, the Control A will repeat the previous input line; Control C is program interrupt; Control D will redisplay the present input line; Control Q is to quit the program; Control W will temporarialy halt data to the terminal, with any other key resuming the output; Control X for line delete; and ESCAPE is for End-of-file.

Most OS-9 software is re-entrant, which makes the most efficient use of memory. If a program that you request has already been loaded into memory by another user, you will execute the same copy instead of loading in another copy of the program and using up more memory. OS-9 also keeps track of how many processes are using each program module and deletes the module when

the last user is finished. Most software also allows you to go back to the Shell without truly "leaving" the program you are running. As an example, when you are in Basic09, you may type DIR to see the BASIC programs loaded into memory at the present time, and Shell DIR to see the program names in the Shell directory. After going to the shell directory, you return to Basic09.

There is a unified I/O system with OS-9 which allows data to be transferred in exactly the same way. This is done with a logical structure used for all devices, using software routines to eliminate any hardware dependencies wherever possible. This makes it possible to write programs that will operate correctly regardless of the I/O devices used. Also, programs may be used on another computer even though it may have different kinds of I/O devices.

The file security system used is ideal for education, office use, or any time you want or need to keep files from the wrong people. Each file has information about certain attributes when they are created, including: Ownership, Date & Time created, date and time of last access, and access permissions. The access permissions may be turned "off" or "on", but only by the FILE OWNER. They may be "public" or "private" and include Write Permit, Read Permit, and Execute Permit. For example, a file that allows public execute, owner write and owner read will prevent the public from reading or writing to the file, but they may run the program.

More than one directory is part of the method of tree-structured hierarchy. This allows you to make directories for various processes and even one or more for each user, if desired. And by doing things properly, you can have a set of test files used to check out a program, and a set of working files, both with the same name. They really don't conflict because the files are on different

directories. Also, ownership and security attributes may be used just like a regular file.

SOME OBSERVATIONS

There are a few things that we felt could be improved after working with the system for a few weeks. One of them is the Manual(s). When approaching Microware about the problem, we learned that the manual we have is a preliminary one, and the new ones will arrive soon. The only thing that was not the best with the manuals that we received is that there are places that a little more explaination would have helped a lot. Also, a few of the examples given don't work as written. We're confident that the problem has been Taken care of.

Since the system needs interrupts to accomplish the work, we found that it would have been a lot nicer to have a disk controller board that uses them so there would be no "glitches". This is not a problem with OS-9, but with the disk controller board we used. By the way, one of the other controller boards we used works like a champ and has no interrupt connections, so there could be another problem with the first one.

We found the timesharing mode to be very efficient compared with other small systems we have seen. The line buffer accepts characters even when the system is loading a disk program, etc. The characters aren't echoed back until it has a second to do so, but otherwise most of the normal inputting occurs as fast as you can type. We were only able to experiment with two users up to now, but the slowdown due to two users was very minimal. A lot of disk operations, especially with 5-1/4 inch floppy systems, will make timesharing quite slow, but running programs using RAM memory is nice.

We only have two complaints about timesharing -- one deals with the manual again. Since it was a preliminary one, we can assume that it has better instructions for bringing up the timesharing system in it. A file called "password" must be created and what to do after that is not too clear. The second complaint we have deals with going back to single-user operation. How can it be done? Nothing is mentioned in the operations or system preliminary manuals.

Our main observation and conclusion about OS-9 is that it is a powerful operating system that will work with smaller systems as well as larger ones and still gives you "UNIX"-like operations, complete with "pipes" and "forks". True multitasking and multiprogramming features are here with the ability to have several users running one re-entrant program at the same If you are looking for an operating system that is "state of the art", not prohibitively expensive, and one that will be supported by all kinds of users and yet fit in a smaller 6809 system, then the only choice is OS-9.

Microware is a company that you can have confidence in, not only for the delivery of the product, but for exceptional support. As an example of this support and assistance, Microware has installed a phone set aside just for technical assistance and questions. It is available from 9 a.m. to 5 p.m. •(Central Time) Monday through Friday. The number is (515) 279-8898. In talking with the folks at Microware, you can expect to see several new programs offered this summer. One of the first to appear will be their PASCAL which meets the full ISO standards and has floating point and interger math. Also a software "switch" to use either P-code or the optimized code. More on this at a later date.

For further information and pricing on OS-9, contact Microware Systems Corporation, 5835 Grand Ave, Box 4865, Des Moines, Iowa 50304. Also, see the Microware ad in the centerfold of this magazine.

[SS-50]




THE WI

The sixth an Computer Faire wa 5 in San Francisco and Brooks Hall. largest shows in the has something mattend.

Three of the sta although we didn't booth this year. A not the only ones t Out of all the







THE WEST COAST COMPUTER FAIRE

by Ken Orme

The sixth annual West Coast Computer Faire was held April 3, 4, and 5 in San Francisco's Civic Auditorium and Brooks Hall. This is one of the largest shows in the country and always has something new for those who attend.

Three of the staff attended the Faire, although we didn't get set up to have a booth this year. Apparently, we were not the only ones that didn't have one. Out of all the 68XX family, only

Percom Data Company set up a booth. We have received several letters mentioning how disappointed many 68XX people were about the lack of interest from many of the regulars.

Richard Don from Gimix was in attendance and mentioned that they were going to be at NCC in Chicago (as are many others). We did visit with several other people, including Dr. Chuck Adams, Ray Boaz, and Harold Mauch. All of them expressed a desire



to have more of a showing at such a large event.

The offical count for attendance at the Faire this year was 31,729 but was low, due to those who are dishonest and sell their badges on the way out to interested people coming in. There were 520 booths and exhibits, which should give you an idea of the size of it.



Many new ideas were presented and many interesting conference programs were presented, but for the 68XX user this year, most were of general rather than specific interest. In talking with Jim Warren, the chairman of the Computer Faire, we should plan now to have some user's meetings and/or topics of discussion for the next one.

I'm sure that many, many others will agree with us that it would be one of the best public relations efforts that could be given for the 68XX family of processors if at least one meeting out of the 100 held at the Faire were to be based around the 6800 or the 6809. There was at least one meeting held with the 6809 as its base last year. Terry F. Ritter was there discussing "Modular and Structured Programming on Small Systems (Including 6809)

Assembly Language)". In case you don't know, Terry is from Motorola and is one of the best authorities on the 6809 processor in the world since he is a co-architect of the 6809. I'm sure that if we were to have a program dealing with some of the "state of the art" systems software now being produced for the 6809 it would turn a few heads and let people know about the third generation from Motorola.

There are many users in the "Silicon Valley" area and therefore it seems to me that we could stir up at least one meeting for the 68XX people. I realize that there are other shows around the country, and that it is a long haul for some of the hardware and software people, but we will all mutually benefit from attending.

The West Coast Faire seems to draw a lot of technically oriented people and still has the cross section of hobbyists, business systems users, and general "looking for a computer" types. Just by attending the Faire, we found out several things in store for us just ahead.


Some of the booths of interest included the Japan Microcomputer Club with a "sneak preview" of the Hitachi MB6890 (6809 processor) color com-



puter with excell Microsoft was ther them, found out BASIC for not only Computer, but th Also they have a the 6809 that rui may soon be marl Company had n products there inc serial interface c generation on it, price). Also, the was on display alc new products 1 Peripheral last is Percom also had Computing magaz ed to be given people. We would Mauch and the c helped us there.



Many of the n very interesting to 51/4 inch Winches 12.72 Megabytes (u and at a reasonable from RMS (Rotatir Inc.). Even though processor, Adam (with his Osbourne computer that fold carrying case. Pro al was there with t PIE Programma Int is an editor design ressable terminals a video boards using puter with excellent graphics. Also, Microsoft was there and in talking with them, found out that they wrote the BASIC for not only the TRS-80C Color Computer, but the MB6890 as well. Also they have a disk-based BASIC for the 6809 that runs under FLEX that may soon be marketed. Percom Data Company had most of their new products there including the new dual serial interface card with baud rate generation on it, (with a reasonable price). Also, the ColoRAMa-50 board was on display along with most of the new products mentioned in Peripheral last issue. By the way, Percom also had a stack of SS-50 Computing magazines that we furnished to be given away to interested people. We would like to thank Harold Mauch and the other fine folks who helped us there.



Many of the newer products were very interesting to us including a new 51/4 inch Winchester hard disk with 12.72 Megabytes (unformatted) capacity and at a reasonable single quanity price from RMS (Rotating Memory Systems, Inc.). Even though he used the wrong processor, Adam Osbourne was there with his Osbourne 1 personal business computer that folds up into a portable carrying case. Programma International was there with their new 6800/6809 PIE Programma International Editor). It is an editor designed with cursor-addressable terminals and memory-mapped video boards using FLEX. Also, they



mentioned SPL/M (Small Programming Language for Microprocessors) which is a compiler which generates absolute 6800 object code and runs under FLEX. The people from Exatron were there with news that the stringy floppy for the 6809 based TRS-80C will be ready soon. Many of the book companies were present including Osbourne/ McGraw-Hill, Byte Books, Prentice-Hall, John Wiley & Sons, Hayden Books, Howard W. Sam, and Dilithium Press. Most of them have 6800 processor offerings now, and the 6809 books are here or coming shortly. MicroDaSys was there with a new projection on their upcoming 69000 machine. The literature I picked up now says shipments will start June 1981.

We had a wonderful time, and there were so many things to see and do that you really have to pick out the things that are most worthwhile to you and do them first. I had the unique experience of driving to the show and even though it is a long drive, it was most interesting.

Let's get together next year for the show and try to have a group of hardware/software people there as well as 68XX users. The date is set for March 5-7, 1982. See you there!!


[SS-50]



Programma's Booth



Ray Boaz from BOAZ CO. talking with the Percom people



Some of the "System 50" boards from Percom on display at the Faire



Harold Mauch, president of Percom Data Company, talking with some of the many interested Faire goers



Adults and kids alike, all enjoyed the fun and giveaway items



The Osbourne 1 personal business computer drew a lot of attention

"Ope: Patch

With the op published in the we mentioned the program in as we then save it as in user's manual. In have been think manual because mention the me without a personal ning and ending may be saved in date prompt is no

In order to he to give the prop "patched" version following:

- 1. Besure to v when doing the will insure that "FLEX2.SYS" to something goes insures that you v that give the date
- 2. Write the p making certain th the right place (or sure that you as uration to the p

The "Open Door" Patch Revisited

With the open door fix that we published in the Nov/Dec 1980 issue, we mentioned that you could key the program in as we gave it to you, and then save it as instructed in the FLEX user's manual. It seems that we must have been thinking of the MiniFLEX manual because FLEX 2.0 doesn't mention the method to re-save FLEX without a person knowing the beginning and ending addresses, and then it may be saved in such a way that the date prompt is no longer given.

In order to help with this, and also to give the proper method to save a "patched" version of FLEX, we give the following:

- 1. Besure to work with FLEX.COR when doing the modifications. This will insure that you have a correct "FLEX2.SYS" to use in the event that something goes wrong. This also insures that you will get a version saved that give the date prompt as it should.
- 2. Write the patch using the editor making certain that you get the ORG in the right place (or places). Then, make sure that you add the proper configuration to the program starting with

				260	11014		
					HAM	OPENDOOR	
BF90					ORG	\$BF90	
BF98	7E	BF	B1		JMP	\$BFB1	
				2∯¢			
BFB1					ORG	\$BFB1	
BFB1	F6	80	19		LDA B	\$8019	
BFB4	F7	80	18		STA B	\$801B	
BFB7					LDA A	#\$1B	
BFB9			13		STA A	\$8018	
BFBC	SD	E2			BSR	\$BFA0	
BFBE			88		LDX	#\$4000	
BFC1					LDA B	\$8018	
BFC4					DEX	40020	
BFC5		11			BEQ	\$BFD8	
BFC7					BIT B	#\$82	
BFC9					BNE	\$BFC1	
BFCB							
		30	19		LDA B	\$8018	
BFCE					DEX		
BFCF					BEQ	\$BFD8	
BFD1					BIT B	#\$02	
BFD3		F6			BEQ	\$BFCB	
BFD5					CLC		
BFD6	20	CS			BRA	\$BFRØ	
BFD8	C6	80			LDA B	#\$80	
BFDA	OD.				SEC		
project project project	men				BB - BB - AB - AB - AB - AB - AB - AB -		

OR AN INVALID DRIVE REQUESTED.

THIS PROGRAM IS A PATCH TO TSC FLEX 2.0 WHICH WILL GIVE A 'DRIVES NOT READY' ERROR IF A DOOR IS LEFT OPEN, A DISK NOT INSERTED.

DELLO				UKU	⊅BEH3		
BEA3	E1	AC	INVEC	FDB	\$E1AC		
BEA5	E1	D1	OUTVEC	FDB	\$E1D1		
BEA7	30	94	ACIA	FDB	\$8004		
BEA9	30	12	TIMER	FDB	\$8012		
BEAB	A@	99	IRQ	FDB	\$R000		
BEAD	A0	12	SWI	FDB	\$8012		
BERF	EØ.	DØ	MON	FDB	\$E000		
BEB1	RØ	48	PUC	FDB	\$8048		
				END	\$8D88	005	TRANSFER

* CONFIGURATION FOR FLEX.COR

NO ERROR(S) DETECTED

\$BEA3. (See the program listing.) Notice that the transfer address is listed with the END of the program.

- 3. Next, assemble the patch with the ASMB command. It sometimes pays to use the "+B" option the first time to make sure that no errors have made their way into the program.
- 4. After the patch is assembled, use the APPEND command to append FLEX.COR and the patch together. We prefer to use a different name for the patched version, rather than deleting the old one. Or, at least include a new version number when you write the patch.

Using this technique, you will find that it eliminates a lot of extra work and disappointment trying to use SAVE.LOW with the current working version of FLEX.

[SS-50]

BASIC BUG

DIM Routine Not Very Bright

Geoffrey A. Gass 5240 S. W. DoschRd. Portland, Oregon 97201

There's a minor bug in at least some of the distributed copies of SWTPC Disk BASIC 3.5 for the 6800, bundled with FLEX 1.0 for the DMAF-1 dual 8 inch disk.

The program rejects multiple DIM statements of the form.

10 DIM A(10),B(15),C(5)

with irrelevant error messages such as "ERROR #30 (illegal disk file number) IN LINE #10" -- though statements of the form

10 DIM A (10): DIM B(12): DIM C(5) are accepted.

The problem is in a wild offset in a branch instruction at address \$1721. Instead of an offset of \$C8, the code reads \$C2, branching back, not to the reentry point in the DIM routine for the next variable, but to the third byte of a three-byte instruction.

Luckily, the error just causes a peculiar error message, and does not chew up BASIC, crash the disk, or do any of the other things predicted by Murphy's law.

Change the \$C2 at \$1721 to \$C8 and the bug will go away.

[SS-50]

INTRODUCTING...

Peter Bendall from West Germany

Peter Bendall has lived in or near Hamburg for the last six years. He is English, and works for a lab as a "computer engineer" and with the help of a 'computer scientist' runs the computer part of the support group of the out-station in West Germany.

Mr. Bendall has been in computing or electronics since leaving school, and has lectured on programming minicomputers at a teachers' training college and a local Computer Club sponsored evening classes. He has had papers in the last three DECUS (Digital Equipment Users) symposiums in Bonn and Esslingen, and hopes to have a joint one in the next English DECUS at Warwick.

Peter is married and the father of five children, two of which have left home to start their own families. He took up home computing when he moved into an apartment where he could no longer use his Ham station. Mr. Bendall constructs his own equipment, either from kits (like his own 48K 7768) or from scratch. This has rubbed off onto his work where he is using the F & D CPU-2 to connect an electric typewriter to their lab's PDP-11s. He is also in possession of a radio-teletype terminal unit which is up and functional. It works really well with his mechanical RTTY machine and hopes to get it receiving on the 6800 system soon. There is a UHF RTTY relay about 25 miles away and hopes to later be able to work other Ham stations.

Peter also has an acoustic coupler, and would like to get a second with both originate and answer, and successfully has loaded S1 format from long distances.

We certainly appreciate this article from Peter Bendall, and to learn about the 6800 system in our European countries.

SS-50

The story of 680 is not the story of the in the USA. By the one English compar own designed 6800 l. In Spring 1980, one of at the Hannover Tracthere were more Ex Europe than SWTP ined! Various factor European 6800 a horn the native European based their syste electronic boards.

In England, Netook the 8 inch sq system with its 78 p and designed the 77-6 kit system. The use which either contain or add a complete system. The basic (in that it is fully buff external decoding whan enlarged system. own 5 volt supply, address switches, and

SS-50 OR ONE MAN'S VIEW OF 6800 IN EUROPE

By Peter Bendall

The story of 6800 micro-computing is not the story of the SS-50 bus as it is in the USA. By the end of 1980, just one English company was offering its own designed 6800 kits for the 50-bus. In Spring 1980, one of the Motorla men at the Hannover Trade Fair claimed that there were more Exorcisor systems in Europe than SWTP and Gimix combined! Various factors have made the European 6800 a homebrew system, and the native European designers have based their systems on existing electronic boards.

In England, NewBear Computing took the 8 inch square "Veroboard" system with its 78 pin edge connector and designed the 77-68, a 625 kHz 6800 kit system. The user buys "Bear Bags" which either contain a complete system or add a complete function to the system. The basic CPU kit is unusual in that it is fully buffered and needs no external decoding when incorporated in an enlarged system. The user adds his own 5 volt supply, 8 each Data and address switches, and 8 LEDs to operate

Because of the full buffering, the user can wire a motherboard and add a monitor board (2 ACIAs and 1K RAM, plus a 32 byte 'bootstrap' program) and extend later with 4K and 32K RAM, EPROM and PIA boards to a 48K system with 8 inch hard-sectored disks. NewBear supply the Cottis-Blandford Kansas City Interface kit, suitable for any ACIA or UART interface, which provides 300, 600 and 1200 baud as well as 2400 baud 'non-redundant' recording speeds. The German branch of the user group have just announced an SS-30 adapter card which allows the use of the JPC products TC3 and the CFM3 operating system as well as other 30 pin I/O cards.

EUROCARDS

Eurocom-I, the German offering from ELTEC, has used the standard 4 inch x 6 1/2 inch 'Eurocards' with its standard 64 pin bus connector. This 1 MHz 6802 system uses a double width, 8 inch, CPU card with a Hex keypad and 8 Seven segment displays and has

1K extra RAM and a monitor in two 2708s. The Kansas City Interface is on board. Changing the EPROMs and adding a keyboard and the video interface board to the on board PIA, converts the system to an ASCII type monitor. A 16K RAM can be connected to the unbuffered bus connector.

The popularity of Eurocom has attracted several small companies to produce Eurocom 'add-ons' such as memory and I/O boards. Because of the standard Eurocard, the 6502 systems have also produced very similar ranges of boards with a bus that is almost exactly the same as that of the 6800 systems, so that accessories such as buffered motherboards, memory extensions and I/O boards can be used with almost no modifications needed.

CLUBS

The overall club scene in Europe is that a large number of local clubs and one-system user groups. A notable exception is the 'Amateur Computer Club' in England, though it is itself large enough to support local interest groups united through the newsletter 'ACCumulator', and backed up by libraries for the main micro-processor families. The ACC was responsible for a lot of the original interest in the 7768 system as it published the circuits for the system and a lot of the 7768 software in earlier issues of its newsletter.

Several groups and clubs sprang up out of Radio Club or Computer Club construction projects, and from evening classes in microcomputing. One problem that hits the European user whnen leaving the beginning phase is how to obtain suitable software at affordable prices and getting it to run on his system when he can get it. Both 7768 and Eurocom--I have monitors at \$Fxxx, and non-standard IO addresses.

The 7768 has also unusual 40 x 24-line VDU display at \$F800. The various clubs collect and distribute the essential patches to allow the user to run his system with the software when he gets it.



18

A German spe 7768 user group of following the tran construction manu its use in a club pr in Harburg, North on the following some users in Au Germany as well European postings. Own library with articles from German text version programs, and pate programs.

RADIO H

Another gronearly all Radio H from the quarter which is sponsor amateur radio club covers all 68xx mainframes. It spead hardware of an Morse-code and radin its library, a programs for Ham 1

Both ELTEC w NewBear with 79 6809 systems. ELT 48K FLEX compati to run form, whe chosen to supply a (a single card that is other kits and is S The program is t reasonable priced so compatibility has any company likes t and addresses of it I'll see that it gets p lot of work to do getting down to it.

Please m SS-50 Co when cor Advertise A German speaking branch of the 7768 user group came into existence following the translation of the '7768 construction manual' into German, and its use in a club project by a radio club in Harburg, North Germany. There are now users in Austria and Southern Germany as well as servicemen on European postings. The group has its own library with reprints of 68xx articles from German magazines, German text versions of many BASIC programs, and patches for various 6800 programs.

RADIO HAM USERS

Another group of 68xx users, nearly all Radio Hams, has developed from the quarterly magazine ASCI, which is sponsored by the German amateur radio club DARC. This group covers all 68xx processors, and all mainframes. It specializes in programs and hardware of amateur interest, with Morse-code and radio-teletype programs in its library, as well as BASIC programs for Ham use.

Both ELTEC with Eurocom-II and NewBear with 79-09 have developed 6809 systems. ELTEC has a complete 48K FLEX compatible system in ready to run form, whereas NewBear have chosen to supply a CPU and Monitor on a single card that is compatible with the other kits and is SWBUG compatible.

The program is to find suppliers of reasonable priced software now address compatibility has been achieved! If any company likes to tell me the names and addresses of its European agents, I'll see that it gets published. There's a lot of work to do and the clubs are getting down to it.

[SS-50]

Please mention SS-50 Computing when contacting Advertisers.



Letters

Dear Editor,

I am hoping to start a club in the Northern New Jersey/New York City/Long Island area for anyone interested in building or working with robots. I would like to get a list together of all the people interested in joining such a club or working with robots.

Even if you are too far away to attend a meeting, keep in touch with me. I might hear of a local club in your area.

The meeting time and place have not been picked yet, but will probably be on a week night in New York City.

If you have any questions or problems with robots, write me, I might be able to help.

David Smith

Dear Editor,

I'd like to try the "FLEX Open Door Patch" on page 17 of your Nov-Dec 1980 issue. I can't figure out how to save the patched copy of FLEX on the disk. Your statement that "Addresses and methods are in you (sic) FLEX user's guide." may be true, but I can't seem to find them.

Help!

Paul Pennington

See the Article in this issue.

Editor

HITACHI MB-6890

One of the biggest attractions at the West Coast Computer Faire, was the HITACHI MB-6890 Computer. The hallway near the Japan Microcomputer Club exhibit (where the MB-6890 was located) was almost always crowded to the point that you couldn't get through. Even though Hitachi was not displaying their new arrival for the purpose of selling it, there was surely a lot of interest as to when it would be sold here and how much it would cost.

The heart of the system is the 6809 microprocessor and therefore should be of interest to most of us. In the basic setup, the MB-6890 contains 32K of RAM (expandable to 62K on board), and a 24K BASIC in ROM (from \$A000 to

\$FF00) with I/O located from \$FF00 to The system has beautiful, full-color, high resolution graphics that puts many systems to shame. It comes with a built-in 600 baud cassette tape interface, a built-in light pen, an RS-232 interface, a parallel port, and a video output. The 640 x 200 high-resolution graphics display looks very good on the optional C14-2170 video monitor designed to match the system. available is the dual floppy disk drive (MP-3540), which interfaces to the machine easily. The light pen plugs into the machine via a 5 pin connector with internal decoding and BASIC commands for it built-in. An eight pin connector is used to output video



information from circuitry includi: vertical sync pulse green color inform


The word is th MICROSOFT. It extended BASIC w features that are MB-6890. Some unique to this LOADM, SAVEM PAINT, SCREEN, (Used for DATE\$, SCREEN, COLOR LIGHTPEN, and modifications.). GOTO, PEN, and The BASIC is very many variations programs as well It features single 7.1 digits and dou digits. Long varia characters) are allo nice screen editing

The case featur additional boards t bus with access available on the RS-232 connecto connector, the vid a cassette tape cor color video connec consists of a 56 connector, with signals available (r the upper right-l case, a small cor open to allow a switch, the volu sound, a mode s' switch. The keyl with a 23 key nu right. There are programmable fu numeric keypad multiply, and div control keys, a re others. The key iapanese "Hiragar able in the shift marketed in the 1 have upper and lov

information from the computer video circuitry including horizontal and vertical sync pulses, and red, blue, and green color information.

The word is that the BASIC is from MICROSOFT. It appears to be a good, extended BASIC which includes several features that are developed for the MB-6890. Some of the commands unique to this system include: LOADM, SAVEM, EXEC, NEW ON, PAINT, SCREEN, INPUTWAIT, KEYn (Used for DATE\$, TIME\$, TERMINAL, SCREEN, COLOR, LOAD, LIST, RUN, LIGHTPEN, and CONT single key Also, ON COM modifications.). GOTO, PEN, and ON PEN - GOSUB. The BASIC is very complete and allows many variations in graphic oriented programs as well as regular programs. It features single precision variables at 7.1 digits and double precision to 16.8 digits. Long variable names (up to 15 characters) are allowed and it has some nice screen editing features.

The case features room for up to six additional boards to be connected to the bus with access out the back. Also available on the back is a standard RS-232 connector, a parallel port connector, the video output connector, a cassette tape connector, and the 8 pin color video connector. The bus system consists of a 56 pin card-edge style connector, with the normal SS-50C signals available (plus a few others). In the upper right-hand portion of the case, a small compartment door will open to allow access to the power switch, the volume control for the sound, a mode switch, and the reset switch. The keyboard is standard size with a 23 key numeric keypad to the right. There are 59 ASCII keys and 5 programmable function keys. numeric keypad has add, subtract, multiply, and divide keys, the cursor control keys, a return key and a few others. The keyboard we saw had japanese "Hiragana" characters available in the shifted mode, but when marketed in the U.S. it will probably have upper and lower case letters.



The advertised prices in Japan are 298,000 Yen for the MB-6890 alone. The color monitor is 168,000 Yen, and the dual disk system sells for 298,000 Yen. Although we don't have the means to find the current exchange rate locally, those of you that are interested can probably find out.

A bit more on the graphics. This machine has one of the best graphics displays we have seen. A few others will top it, but not within the price range. The fact that the screen will display 25 lines of 80 characters or 25 lines of 40 characters lets you know that you can probably select high or low resolution graphics. Well you can select not just two, but four resolutions bysoftware control. They include: 640 x 200 dots or 320 x 200, 160 x 100, and 80 x 100 with color. Speaking of color, the display can contain both characters and graphic symbols with 6 colors besides white and black and will allow you to specify both foreground and background color. Some systems have more colors than this, but most are very limited on the high resolution end of things.

This article is not meant to be a sales pitch for Hitachi, since we don't know if the machine will ever be available here, but mostly because of the interest from you. If any of you readers have other news of this machine, feel free to share it with us.

[SS-50]

Editor's Note -

We would like to thank Richard Keightley for first calling our attention to this Computer.

Flex and OS-9 on the SWTPc 6809

by Gary Manning

If you have been interested in getting OS-9 for your 6809 system, but still want to be able to use your present software, you can have it both ways at the flip of a switch if you have a Southwest system with a MP-09 board (and probably most other systems as well). All it will cost you is a double pole double throw switch, some wire, and an optional four pin connector and plug.

The OS-9 firmware for a Southwest system consists of three 2K (2716 type) ROMs. Microware intends for two of the ROMs to be placed in a ROM board and ROM No. 1 to replace the monitor at \$F800-\$FFFF. The other two are position independant and can be located most anywhere in the memory space. Since the MP-09 board has three ROM sockets, I thought, "Why not use them?" These sockets are intended for use in small dedicated applications such as single board controllers, etc. Their use in a system is discouraged, but they can be used if you know how.

The address and use of the MP-09 ROM sockets are as follows:

Socket No. 4 (\$F800-\$FFFF) is for the monitor and cannot be disabled. Socket No. 3 (\$F000-\$F7FF) is enabled or disabled by the fourth switch in the switch block S1. The address area is reserved for DMA devices, so if you don't have any, you're okay so far. Socket No. 2 (\$E800-\$EFFF) is enabled or disabled by S1, #3. This address area is reserved for upper I/O and should be unused on most systems. Socket No. 1 (\$E000-\$E7FF is enabled or disabled by S1 - #2. This address area conflicts with I/O and cannot be used as it is, but this socket can be re-addressed.

The secret of being able to switch operating systems, is to have two sockets addressed at \$F800-\$FFFF (one for each monitor) and switching to select one *or* the other. Sockets No. 1 and 4 will be used this way, the other two need not be modified.

You may have some reservations about all of this because it seems too simple, but it gets better. Since FLEX and SBUG-E don't care about memory from \$E080-\$F7FF, you can leave the OS-9 ROMs 2 and 3 enabled in this area all of the time. If you can't place the ROMs in this area, you will have to devise a means to disable them so that they don't conflict with FLEX. Also, I had some questions about how the Dynamic Address Translator (DAT) would behave under OS-9, but we have never had any problems with it since installing OS-9. One thing that is required with OS-9 is that all of your memory must be in a contigious block.

Before beginning to modify the CPU board, you need to consider if you want to place the switch on the CPU board. or on the front panel of the cabinet. For the switch on the front panel, you should find a four conductor plug and connector similar to the abort/reset connector so you will be able to remove the board from the system when desired by simply unpluging the switch connector. You should also consider where you will mount the switch. I used a small toggle switch which I mounted in the black stripe above the reset switch. By mounting the switch in the black stripe, I could cover the hole with a new piece of black tape if I ever decided to remove the switch.

The modification is simple, but a little difficult to explain. Make sure you understand before you do it. First, the select traces to ROM sockets No. 1 and 4 must be cut. For socket No. 4, the trace runs from IC #6 - pin 13 to ROM socket #4 - pin 18 and 20. This trace can be best accessed as it comes down from IC #6 - pin 13 on the front of the board, just to the left of the processor chip. Make sure you have

the right trace, the some small insulat of the cut. If you wire, use both to straight. For sock runs from S1 - #2 to pins 18 and 20. Be pull-up resistor (Ré of the cut, not the best place to cut back of the CPU bo the lower left-mos from the back side. along the top of feed-through just a the trace about ha two rows of pins Again, solder a wire cut, but use the san as you used for soc words, make sure side of both cuts of the socket side cod-

Carefully mour switch on the CPI drill holes and mo room (depending of connector), or glue 'instant' glue. It to ground the switch static protection.

Carefully route switch or connect some glue will kee the board. The D illustration is divide and has the comm center of each ha reference and adjust switch you use. used) will be discus

Connect the so No. 1 to one of the then connect the so No. 4 to the other Next, the select si sould be connect terminal above the switch terminal bel the other side. Cor the two remaining connector is used polarized, wire it as

the right trace, then cut it and solder some small insulated wire to each side of the cut. If you have two colors of wire, use both to help keep things straight. For socket No. 1, the trace runs from S1 - #2 to ROM socket No. 1 pins 18 and 20. Be careful to leave the pull-up resistor (R6) on the select side of the cut, not the socket side. The best place to cut this trace is on the back of the CPU board. Socket No. 1 is the lower left-most socket as viewed from the back side. Its select line runs along the top of the socket to a feed-through just above pin #24. Cut the trace about halfway between the two rows of pins of socket No. 1. Again, solder a wire to each side of the cut, but use the same color for each side as you used for socket No. 4. In other words, make sure you have the select side of both cuts coded the same and the socket side coded the same.


Carefully mount the connector or switch on the CPU board. You may drill holes and mount it if you have room (depending on the size of the connector), or glue it on with epoxy or "instant" glue. It would also be wise to ground the switch housing for some static protection.

Carefully route the four wires to the switch or connector. You may find some glue will keep them "tacked" to the board. The DPDT switch in the illustration is divided by the dotted line and has the common terminal in the center of each half. Use this for a reference and adjust if necessary for the switch you use. The connector (if used) will be discussed later.

Connect the socket side of socket No. 1 to one of the common terminals, then connect the socket side of socket No. 4 to the other common terminal. Next, the select side of socket No. 1 sould be connected to the switch terminal above the common, and to the switch terminal below the common on the other side. Connect select No. 4 to the two remaining terminals. If the connector is used, and it is non polarized, wire it as shown so that if it

is reversed, it will only affect the switch position, but will still work.

Plug OS-9 ROM #1 in socket No. 1, plug OS-9 ROM #2 in socket No. 2, plug OS-9 ROM #3 in socket 3, and leave SBUG-E in socket No. 4. Place the jumpers for sockets 1-3 in the ROM position. Set the switches on S1 as follows: #1 - always on, #2 - must be off, #3 - on and #4 - on. Place the CPU on the motherboard, plug on the connectors and turn on the power. If you haven't predetermined which monitor is selected by one position or the other, you will come up in one or the other (of course). If you come up in SBUG-E, you will get the usual prompt. However, if you come up in OS-9, the disk drive #0 will come on. After you insert the OS-9 disk, the system will load, and the OS-9 prompt will appear on the screen. To change monitors. simply flip the switch and hit reset.



If OS-9 fails to come up, switch over to SBUG and try it. If it won't come up either, then you have a wiring error. If SBUG works but OS-9 doesn't, make sure that your memory is in a contigious block from \$0000 up, and check your wiring.

We have had our system running this way for several months now and have had no problems with it.

[SS-50]

OS-9™LEVEL TWO MULTIUSER OPERATING SYSTEM

rue multitasking, multiuser OS for timesharing or real-time control applications.

Sophisticated memory management permits use of over one megabyte.

Versatile, easy-to-use input/output supports multiple devices.

■ UNIX™-like file structure including hierarchical directories, pipes, filters, and byte-addressable random access files.

Provides log-on password protection and user file security.

Can run on small, inexpensive systems with floppy disks and as little as 32K memory.

□ \$495.00*

OS-9™ LEVEL ONE OPERATING SYSTEM

ingle-user, single-memory map compatible subset of Level Two for software development or stand-alone control applications.

■ Versatile input/output system can support multiple devices using interrupt-driven, DMA, or programcontrolled data transfer. Users can easily add additional I/O devices.

■ Tape or disk-based versions available.

■ Disk versions support UNIX™-like hierarchical directory structure and byte-addressable random-access files.

■ Memory management for single address-space (up to 64K).

☐ Disk version \$150.00*

☐ Tape version \$95.00

BASIC09™ PROGRAMMING LANGUAGE SYSTEM

xtended BASIC language compiler/interpreter with integrated text editor and debug package. Runs standard BASIC programs or minimally-modified PASCAL programs.

Permits multiple named program modules having local variables and identifiers. Modules are reentrant, position independent and ROMable.

Additional control statements for structured programming: IF ... THEN ... ELSE, FOR ... NEXT, REPEAT ... UNTIL, WHILE ... DO, LOOP ...

INTRODUCING

BY MICROWARE

ENDLOOP, EXITIF ... ENDEXIT.

data types: byte, integer, 9 digit

☐ Disk or tape \$195.00*

Level Two.

floating point.

renumbering.

formatted output.

☐ Disk or tape \$250.00

floating-point, string and boolean.

Allows user-defined data types and

complex data structures. Five built-in

Extremely fast program execution.

Available on ROM, disk or cassette

tape. Runs under OS-9™ Level One or

MICROSOFT

6809 BASIC

for the 6809 and OS-9™.

single precision and double precision

Program trace and edit capabilities.

Four data types: integer, string,

Automatic line numbering and

Supports random and sequential

file I/O. Full PRINT USING for

tandard Microsoft BASIC optimized

Search, change and extend operations. Permits multiple input/output files.

OS-9™ INTERACTIVE ASSEMBLER Compact Motorola compatible

and edited.

commands.

assembler for machine language program development.

Buffer, line and character oriented

☐ Disk or tape \$75.00

☐ ROM set (2716) \$90.00

Operates in "batch" mode or interactive line-by-line mode.

■ Facilities for generation of OS-9™ memory modules and system calls.

Formatted listings include syntax and context error checking.

Runs on OS-9™ Level One or Level Two.

☐ Disk or tape \$75.00

☐ ROM set (2716) \$90.00

OS-9™ INTERACTIVE DEBUGGER

acilitates testing and debugging of machine- language programs.

Includes common "monitor" functions: memory examine/change, breakpoints, display/change registers, hexadecimal arithmetic, etc.

Access to system command interpreter.

Available on ROM, disk or cassette tape.

☐ Disk or tape \$35.00 □ ROM (2716) \$50.00

BASIC 09 is a trademark of Motorola. OS-9 is a trademark of Motorola and Microware*. UNIX is a trademark of Bell Telephone Laboratories.

Most software is available on ROM, diskette and tape in versions for many popular 6809 computers. Source listings and yearly maintenance/update service are sold separately for most programs.

*Specify manufacturer and type of CPU and I/O controllers. Contact Microware® for specific availability.

OS-9™ TEXT **EDITOR**

inimum-keystroke macro text editor useful for text preparation or interactive word processing.

User-defined macros with parameters permit virtually unlimited command expansion. Macros can be saved, loaded



MICROWARE.

Microware Systems Corporation 5835 Grand Avenue, Box 4865 Des Moines, Iowa 50304 (515) 279-8844

A/BASIC COMPILI

his BASIC compiler ger pure, fast, efficient 680 language from easy to source programs. Uses ultra-fast integer math, extended string functions, boolean operators and real-time operations. Output is ROMable without any run-time package versions have disk I/O stateme require 12K memory and host Cassette version runs in 8K au requires RT/68 operating syste ☐ Disk Extended Version 2.1

SSB or FLEX* Diskette \$15 Cassette Version I.O. \$65.(

A/BASIC SOURCI **GENERATOR**

n "add-on" option for Compiler disk versions an extra third pass wh ates a full assembly-language listing and assembly language Uses original BASIC names and BASIC source lines as commer

SSB or FLEX* Diskette \$75

A/BASIC INTERPRE

ere it is - a super-fast compiler! Now you ca actively edit, execute ABASIC programs with the eas terpreter - then compile to sul machine language. Also a supe alone applications and controlinterpreter. Requires 8K RAM.

tylograph is a full-featu cessing program for cre Stylograph's interactive engineered features make it th kind of document-preparation commands and real-time screen curate picture of what the prin

Powerful Editing Command The display cursor can be mov by-line, or page-by-page in any of "cut-and-paste" edit commai moved, copied, searched for, re global replace" command sea of a given text string and allov with another string. In the "in: actually formatted before your

A/BASIC COMPILER

his BASIC compiler generates pure, fast, efficient 6800 machine language from easy to write BASIC source programs. Uses

source programs. Uses ultra-fast integer math, extended string functions, boolean operators and real-time

operations. Output is ROMable and runs without any run-time package. Disk versions have disk I/O statements and require 12K memory and host DOS. Cassette version runs in 8K and requires RT/68 operating system.

☐ Disk Extended Version 2.1
SSB or FLEX* Diskette \$150.00
☐ Cassette Version I.O. \$65.00

A/BASIC SOURCE GENERATOR

n "add-on" option for A/BASIC Compiler disk versions that adds an extra third pass which generates a full assembly-language output listing and assembly language source file. Uses original BASIC names and inserts BASIC source lines as comments.

SSB or FLEX* Diskette \$75.00

A/BASIC INTERPRETER

ere it is - a super-fast A/BASIC compiler! Now you can interactively edit, execute and debug A/BASIC programs with the ease of an interpreter - then compile to super efficient machine language. Also a superb standalone applications and control- oriented interpreter. Requires 8K RAM. The cassette

INNOVATION AND PERFORMANCE

5 6800 MIKE an in power of the power of the

BY MICROWARE

version is perfect for Motorola D2 kits.

☐ Cassette, SSB or FLEX* Diskette \$95.00

LISP INTERPRETER

he programming Language LISP offers exciting new possibilities for microcomputer applications. A highly interactive interpreter that uses list-type data structures which are simultaneously data and executable instructions. LISP features an unusual structured, recursive function-oriented syntax. Widely used for processing, artificial intelligence, education, simulation symbolic, and computer-aided design. 6800 LISP requires a minimum of 12K RAM.

Cassette, SSB or FLEX*
Diskette \$75.00

*FLEX is a trademark of Technical Systems Consultants

RT/68 REAL TIME OPERATING SYSTEM

MIKBUG — compatible ROM that combines an improved monitor/debugger with a powerful multitasking real-time operating

lutasking real-time operating system. Supports up to 16 concurrent tasks at 8 priority levels plus real time clock and interrupt control.

Thousands in use since 1976 handling all types of applications. Available on 6830 (MIKBUC-type) or 2708 (EPROM-type) ROM. Manual is a classic on 6800 real-time applications and contains a full source program listing.

- ☐ RT68MX (6830) \$55.00
- RT68MXP (2708) \$55.00

6800 CHESS

challenging chess program for the 6800. Two selectable difficulty levels. Displays formatted chess boared on standard terminals. Requires 8K memory. Machine language with A/BASIC source listing.

☐ Cassette, SSB or FLEX* Diskette \$50.00

Our software is available for most 6800 systems on cassette or diskette unless otherwise noted. Phone orders welcomed. We accept MASTERCHARGE and VISA. We try to ship orders within 24 hours of receipt. Please call or write if you require additional information or our free catalog. Microware* software is available for OEM and custom applications.

MICROWARE.

Microware Systems Corporation P.O. Box 4865, Des Moines, IA 50304 (515) 279-8844

STYLOGRAPH WORD PROCESSOR FOR OS-9"

tylograph is a full-featured screen-oriented word processing program for creating and printing documents. Stylograph's interactive operation and humanengineered features make it the most accurate and easy-to-use kind of document-preparation system. Cursor-based editing commands and real-time screen refresh always gives an accurate picture of what the printed document will look like.

Powerful Editing Commands

The display cursor can be moved character-by-character, line-by-line, or page-by-page in any direction. The full compliment of "cut-and-paste" edit commands permit blocks of text to be moved, copied, searched for, replaced and deleted. The "global replace" command searches for each occurance of a given text string and allows selective replacement with another string. In the "insert" mode the text is actually formatted before your eyes as you type!

■ Complete Formatting Control

Text or individual lines can be center, left, right, or left-andright justified; page and line width can be specified; multiple tabs can be set anywhere. You can define page heading, footers, page numbering, identation and line spacing.

■ Versatile Video Terminal Interface

The basic Stylograph module uses a "personality module" to define the display control codes used by many brands of video terminals and memory-mapped video displays including: Hazeltine 1400/1500 series; Lear-Seigler ADM3-A; GIMIX 80x24; SWTPC CT-82 and 8212; and ADDS Regent series.

□ \$175.00

☐ For proportional printers \$195.00

MICROWARE.

5835 Grand, Box 4865, Des Moines, IA 50304 • (515) 279-8844

BOAZ 64K Dynamic Memory Update

By Ken Orme

Since the article was written on the BOAZ 64K Dynamic Memory Board, we have a few other things that should be mentioned. Those of you who have the early versions of the board will find that there may be a problem with extended addressing as is. This is due to an error that occured on the board, not in the design of the memory board circuitry. However, we received an update shortly after the article was written, explaining what to do to use the board with extended addressing. Since we had not tried it, we assumed that it worked as well as the rest of the board. The fix is simple, and is now corrected on the boards being produced currently, but we mention it here mainly if someone has a board and desires to use it with extended addressing and needs the update, they can write to BOAZ Co. to get the information, or we would be happy to provide a photocopy.

One of the points that we should bring up is that the manual being furnished with the memory board is now much improved and is very good at explaining the jumpers and addressing. We were shipped a preliminary manual and that is why we had the comments on it.


All the IC's that are furnished with the BOAZ boards are tested before shipping to insure that they are in proper working order. I'm sure that is why almost every single kit has worked the first time (according to the last word we received).

There are a couple of new things that are possible with the board for those that are interested. The memory as designed will operate at basic clock frequencies of 898.5 Khz to 1 Mhz. Included with the latest documentation is a modification to allow the board to operate at 1.25 Mhz. This covers the range of the MP-A and MP-A2 as well as the higher rate for 8 inch floppy operation. Also, for those that have DMA disk controllers, there is an outboard modification that you may make to allow you to use both the BOAZ Dynamic memory and the DMA controller. You should write Ray Boaz directly for this modification if it is

One note of interest about the future. Ray Boaz informs me that he has one board using the new 64K Dynamic RAM chips operating. It only requires 8 of these chips for 64K! Imagine, with the board filled up, having 256K of memory on one board. When the 256K chips bit the market, we will be able to have 1 Meg of memory on one board! Also, the 2 Mhz version of the board may come soon.

If any of you need further information, be sure to drop the folks at BOAZ Co. a line. Ray has been excellent to work with, and I'm sure that he will be glad to help any way he can. BOAZ Co., Box 18081, San Jose, CA 95158, (408) 269-9522.

[SS-50]



AMATEUR R

Your TRS-800 receive and trar RTTY BAUDOT RTTY program i minimum 4K The Color Compexisting T.U. or constructions are p. T.U. from a kit a from a single hardware is interested RS-232 port or computer. The following features:

- 1. Transmit an or 100 WPM and simple BASIC '11 110 to 9600 bauc wpm BAUDOT transmitted.
- 2. A user defir 15 characters) car program will pro when it is first ex
- 3. Three prog pre-loaded with and transmitted of
- 4. A "RY" t transmit a tune-ii
- 5. If you have RTTY and SSTV RAM and alternate features are provision these mod 6. The program CR/LF and auton shifting on BAUL

Version 7.01 cassette and doc Version 7.0 strip 2716 EPROM. O provided EPROM



AMATEUR RADIO SOFTWARE


Your TRS-80C can now be used to receive and transmit Amateur Radio RTTY BAUDOT or ASCII code. The RTTY program is written to run on a minimum 4K TRS-80C Computer. The Color Computer is attached to your existing T.U. or one can be constructed. Instructions are provided to construct a T.U. from a kit and a AFSK modulator from a single XR-2206 IC. The hardware is interfaced through the RS-232 port on the rear of the computer. The software has the following features:

- 1. Transmit and receive BAUDOT 60 or 100 WPM and ASCII 110 baud. By simple BASIC "POKES", speeds from 110 to 9600 baud ASCII and 60 to 133 wpm BAUDOT can be received and transmitted.
- 2. A user defined CW call ID (up to 15 characters) can be transmitted. The program will prompt you for the call when it is first executed.
- 3. Three program buffers can be pre-loaded with up to 256 characters, and transmitted on ASCII or BAUDOT.
- 4. A ''RY'' buffer is provided to transmit a tune-in pattern on RTTY.
- 5. If you have a 16K TRS-80C, both RTTY and SSTV can be loaded into RAM and alternately selected. More features are provided than the ROBOT 800 in these modes.
- 6. The program produces automatic CR/LF and automatic upper-lower case shifting on BAUDOT keyboard entrys.

Version 7.01 (above program) with cassette and documentation - \$20.00. Version 7.0 stripped-down version for 2716 EPROM. On cassette or customer provided EPROM \$15.00.

Also the SSTV software is available with cassette and documentation for \$20.00.

For further information or orders, contact Clayton Abrams (K6AEP), 1758 Comstock Lane, San Jose, CA 95124.



GIMIX 64K CMOS STATIC RAM

GIMIX, INC. announces their new 64K Byte CMOS STATIC RAM BOARD with battery back-up for the SS50/C bus. This board is fully compatible with any of the 6800/6809 DMA techniques. They are guaranteed for 2MHz operation with no wait states or clock stretching required. Ultra-low power CMOS RAM requires less than 1/4 AMP (250 Ma.) at 8V for a fully populated 64K Byte board. It is non-volatile using an on-board nickelcadmium battery. The board retains data even with system power removed. With the battery fully charged, the contents of the memory remains intact for a minimum of 21 days.

Since the entire board can be hardware write protected by a switch located at the top of the board, it can also be used to emulate PROM or ROM memory. This is especially useful during firmware development where frequent software changes must be made.

The GIMIX 64K BYTE STATIC MEMORY is available from stock and is priced at \$1088.64 and a 56K version, socketed for 64K is \$994.56.

For further information, or to order, contact: GIMIX INC., 1337 West 37th Place, Chicago, Ill 60609, (312) 927-5510.

POWER PACK

Computerware (tm) announces its POWER PACK for Radio Shack's new

Color Computer.

The POWER PACK cartridge plugs into the Color Computer's interface slot providing 6K additional RAM memory and a powerful 2K monitor. The monitor provides the sophisticated programmer 33 powerful machine level commands and many utility routines. With its extra memory and routines in ROM, this new POWER PACK allows Computerware and other software sources to supply users with much more sophisticated software on cassette at much lower prices than the ROM packs currently available from Radio Shack. Computerware also includes with the POWER PACK a free cassette of diagnostics for the Color Computer.

Already available for use with the POWER PACK is Computerware's Color Editor (\$24.95), Color Assembler (\$29.95), and Color Invaders (\$19.95)! Since Computerware has long been a leader of quality 6800/6809 products (from monitors, disk operating systems and BASICs to games and general ledger) Color Computer owners can be assured this is just the beginning of a long list of excellent products they will see from Computerware.

The POWER PACK is available directly from Computerware, Box 668, 1512 Encinitas Blvd., Encinitas, CA 92024, (714) 436-3512 at the introductory price of \$159.

COLOR INVADERS

Computerware introduces its Color Invaders on cassette for the Radio Shack Color Computer.

You are at the controls of the Color Computer Space Tank, firing at stellar ships and invading critters. Invading ships burst in air with explosive noise. Alien critters march across the screen dropping bombs and screening as life is zapped from their fried little bodies. Fun?? Yeah!!

With brilliant color, dynamic sound and fast action, Color Invaders offers a continous source of excitement to all players. Each of the 8 levels of play present additional complications keeping the beginner going and the experts challenged.

Color Invaders requires 16K and the POWER PACK to be installed (using the extra memory and powerful commands inside) and is priced at only \$19.95. It is available directly - Computerware, Box 668, 1512 Encinitas Blvd., Encinitas, CA 92024, (714) 436-3512.

A FORTH SOURCE

Mountain View Press, the FOURTH source, has a wide variety of printed publications for the FORTH language. While no machine readable information is handled by Mountain View Press, there is an extensive list of materials available for the installation of FORTH. For \$20.00, to cover the cost of an Installation Manual and a specific Source Listing, FORTH can be implemented on the purchaser's micro computer.

The following Source Listings are available: 8080 (will work on Z80), 6502, 6800, 6809, PACE, PDP-11, and Alpha Micro. All Source Listings are to fig-FORTH standards. "fig" is an abbreviation for the FORTH Interest Group, a worldwide group of over 2500 FORTH users that may be contacted at PO Box 1105, San Carlos, CA 94070.

A number of user and reference manuals and books about FORTH are also available from Mountain View Press. Some of these are: "Using FORTH", "A FORTH Primer", and "Tiny Pascal in fig-FORTH".

For further information contact: Mountain View Press, PO Box 4656, Mtn. View, CA 94040

[SS-50]



Garland, Texas

The effort we expe 6800 software for the rather painfully taug development requires a time and manpower vendors whose sole bu software do well to desingle significant software consequently, when 6809-based products, outside vendor-development vendor-developmen

foundation for both s

CON'

FLEX, UNIFLEX, OS-9
OS-9 on the Percom L
Inexpensive Speech
Implementing Speech
SBC/02 Monitor
New Products
EXORciser Compatible



Garland, Texas

No. 5

FLEX, UNIFLEX, OS-9

by Harold Mauch President, Percom Data Company

The effort we expended trying to develop 6800 software for the LFD-400 disk system rather painfully taught us that software development requires an enormous amount of time and manpower. Even the software vendors whose sole business is the creation of software do well to develop and document a single significant software package in one year! Consequently, when we began to develop 6809-based products, we decided to use outside vendor-developed system software when possible and reserve the in-house software effort for utilities, special drivers, application programs and customer support.

Since a good operating system is the foundation for both system and application

vendors. FLEX/9 by TSC was developed first but was little more than a reassembly of the 6800 FLEX. It was definitely not "FLEXible" enough for the 1/0 intensive applications we envisioned for the 6809. UNIFLEX was still being developed but a review of the design specification revealed it was not practical for control applications because the memory requirement was too large and the 1/0 restrictions were very "unFLEXible".

The preliminary description of OS-9 was interesting. It had the device-independent 1/0

software, we contracted the various software

and UNIX-like features that we had come to appreciate in INDEX, plus the capability of supporting a broad range of hardware configurations ranging from simple ROM-based controllers to multi-tasking multi-user data processing systems. Although it took longer to develop than predicted, the result is well worth the wait. OS-9 is everything we wanted in a 6809 operating system. It was easily configured to run on a PERCOM adapter-modified 6800 computer as well as with the PERCOM SBC/9 MPU in a SYSTEM-50 configuration. Tim McKee of our technical staff performed the implementation and has provided several configurations which are set forth below.

Although most of our current and planned 6809 software development is designed for use with OS-9, the PSYMON ROM operating system and the MPX/9 disk system are still available for users with inexpensive or (uncomplex) 6809 system requirements.

CONTENTS

FLEX, UNIFLEX, OS-9
OS-9 on the Percom LFD-400P2
Inexpensive Speech
Implementing SpeechP4
SBC/02 MonitorP7
New Products
EXORciser Compatible Products

CONFIGURATION 1:

PERCOM SBC/9 with 2716 EPROM, LFD-400 Mini-Disk System, 48K byte memory (contiguous), SYSTEM-50 motherboard and power supply.

	Memory Map
FFFFF800	OS-9 EPROM P1
F7FF-F7FE	Console ACIA
F7FDF400	Room for I/O
F3FFD000	Unused
CFFFCC00	LFD-400 Drive I/O
CBFFC000	OS-9 EPROMs PCM1, PCM2, & PCM3
BFFF0000	RAM

CONFIGURATION 2:

MP-A2 CPU card with PERCOM 6809 Adapter, LFD-400 Mini-Disk System, MP-S serial I/O card, 32K bytes RAM, MP-B or MP-B2 motherboard and power supply.

	Memory Map
FFFF-E800	OS-9 All EPROMS
E7FFD000	Unused
CFFFCC00	LFD-400 Drive I/O
CBFF8020	Unused
801F-8008	Free for I/O
80078004	Console ACIA
8003-8000	Free for I/O
7FFF0000	RAM

CONFIGURATION 3:

MP-A2 CPU card (see note) with PERCOM 6809 Adapter, LFD-400 Mini-Disk System, MP-S serial I/O card, 48K byte RAM, MP-B or MP-B2 motherboard (see note) and p. supply.

	Memory Map
FFFF-F800	OS-9 EPROM P1
F7FF-E020	Unused
E01FE008	Room for I/O
E007 E004	Console ACIA
E003E000	Room for I/O
DFFFD000	Unused
CFFFCC00	LFD-400 Drive I/O
CBFFC000	OS-9 EPROMS PCM1, PCM2, PCM3
BFFF0000	RAM

Note: The MP-A2 and MP-B/B2 boards require slight modifications that are switch selectable. They may be returned to their original configuration by switching them off.

OS-9 ON THE PERCOM LFD-400

by Tim Mckee

Microwave is delivering their LFD-400 (tm) version of OS-9! It seems to work really well.

My first and most important recommendation, however, is: Get the DEBUG package. OS-9 has none of the debug features we have come to know and love. All that OS-9 does is execute a program. You cannot even modify memory without using 'DEBUG'.

DEBUG is perhaps the most extensive debug package that I have seen. It allows the use of complex numerical expressions, including register values and indirect addressing to several levels.

There are many valuable machine language utilities included on the diskette. Using 'DEBUG' and these utilities, you can create diskettes that will 'boot' with the I/O addresses set to whatever value you want.

The first machine that we successfully brought OS-9 up on was -- believe it or not -- a SWTPC 6800 system with a Percom 6809 adapter installed. This was an ordinary 6800 system: MP-A2 CPU card, 32-Kbyte memory from 0-\$7FFF, 8-Kbyte memory from \$A000-\$BFFF, MP-S card at \$8004 and a DC-2 disk controller.

Incidentally, adapting an MP-A2 card with our 6809 conversion card is the least expensive way that I know of to make the transition from a 6800 computer to a 6809. The 6809 Adapter is just \$69.95.

The only limitation of this system is lack of memory for large programs such as BASIC09. Even this limitation can be done away with by remapping the I/O to another address, e.g., \$EXXX, and modifying the processor card slightly.

Helpful Hints:

 To change the number of tracks that will be formatted on a diskette:

SYSTEM	USER RESPONSE	COMMENT	
059: 059:	load format [CR] debug [CR]	[CR] = carriage return	
DB: \$XXXX 87	1) format [CR]		
DB: \$XXXX 23	.p.+39 [CR]		
DB:	=#TT [CR]	TT is (decimal) number of last track to be formatted.	
DB:	q [CR]	q - quit DEBUG	
OS9:	save <name> format [CR] unlink format [CR]</name>	omit angle brackets	

The new format utility may be renamed FORMAT.

2. The device descriptor blocks come with devices set to specific addresses. As long as you can map your terminal ACIA to its proper address once, you may change them as needed:

SYSTEM	USER RESPONSE	COMMENT
089:	debug [CR]	
DB: \$BC09 8	1 pterm [CR]	space bar "character"
DB: \$BC18 F	.	+f adds hex f to address
DB: \$BC19 F	E XX [CR]	XX most significant byte of new console address
DB: \$BClA 1	3 = YY [CR]	YY least significant byte of new console address
DB: \$BC3C 8	15t1 [CR]	tl is an auxillary terminal
DB: \$BC4B E		
DB: \$BC4C 0	= XX [CR]	See note above for XX.
DB: \$BC4D	= YY [CR]	See note above for YY.

Changes for a parallel printer (p) or serial printer (pl) are made similarly.

		1
DB:		liclock [CR]
SBDA	1 87	,
DB:		.#.+b [CR]
SBDA	C EO	1
DB:		=XX [CR]
SBDA	D 50	
DB:		=YY [CR]
SBDA	E 01	
18:		q [CR]
059:		verify term [CR]
059:		verify tl [CR]
059:		verify p [CR]
069:		verify pl [CR]
069:		verify clock [CR]
059:		cobbler <drive> [C</drive>

When OS-9 is "booted have just created, all I the new device address

Data recovery while controller card was very was unable to even the same diskette and no problems after mak DC-2 card.

It seems that SWT separator circuit on the floppy disk controlled Digital recommends modification to controlling a Percommensive module (\$ on eliminating disk R specify that it is to controller.

INEXPENSIFOR YOUR

by Sam

Many techniques processing.

Cost constraints, consideration, often w speech process that is

This article will in artificial speech and low-cost, high-quality 50 computer.

PERCOM's SPEAk module enables a host Texas Instruments' S disabling the SPEAK & and taking control of i

Handshake between through an 8-bit port s (Parallel Interface Ada computer.

Conversion of a accomodate a SPEAK-manent.

DB: SBDA1 87	ljiclock [CR]
DB:	.#.+b [CR]
SBDAC EO	Lang (ca)
DB:	=XX [CR]
SBDAD 50	
DB:	=YY [CR]
SBDAE 01	
DB:	q [CR]
059:	verify term [CR]
DS9:	verify tl [CR]
DS9:	verify p [CR]
0S9:	verify pl [CR]
069:	verify clock [CR]
059:	cobbler (drive)
	•

adds hex b to address

XX most significant
byte of MP-T address.

YY least significant
byte of MP-T address.

Finished changes

Finished changes

Primary terminal
Auxillary terinal
Parallel printer
Serial printer
MP-T
(drive) /D0, /D1, etc.

When OS-9 is "booted" using the diskette you have just created, all I/O will be done through the new device addresses.

Data recovery while using the DC-2 disk controller card was very bad. In one instance, I was unable to even format a diskette. Using the same diskette and the same system I had no problems after making a modification to the DC-2 card.

It seems that SWTP used the internal data separator circuit on the Western Digital 1771 floppy disk controller chip. Even Western Digital recommends against this. The modification to correct this consists of installing a Percom SEPARATOR(tm). This inexpensive module (\$29.95) will work wonders on eliminating disk Read errors. Be sure to specify that it is to go on a SWTP disk controller.

INEXPENSIVE SPEECH FOR YOUR SYSTEM-50

by Sam Campbell

Many techniques now exist for speech processing.

Cost constraints, more than any other consideration, often will determine the type of speech process that is used with a system.

This article will introduce the concept of artificial speech and describe a way to add low-cost, high-quality speech to your System-50 computer.

PERCOM's SPEAK-2-ME-2(tm) interface module enables a host computer to control a Texas Instruments' SPEAK & SPELL by disabling the SPEAK & SPELL controller chip and taking control of its data lines.

Handshake between units is accomplished through an 8-bit port such as the modified PIA (Parallel Interface Adapter) port on your 680X computer.

Conversion of a SPEAK & SPELL to accommodate a SPEAK-2-ME-2(tm) is semi-permanent.

Because there is a fair amount of hardware modification required, you may want to take advantage of the installation service PERCOM offers, although most customers make the installation themselves.

An article by Tim McKee elsewhere in this issue of the Peripheral describes how to connect a SPEAK-2-ME-2-modified SPEAK & SPELL to a 6800 computer.

The production of speech in the human vocal system is a matter of the vocal tract being exercised by air from the lungs. There are two kinds of excitation, periodic and random. Periodic excitation is caused by the vocal folds blowing apart and collapsing under lung pressure. Random excitation is created by air rushing over the articulators -- lips, tongue and teeth -- with the vocal folds open.

The vocal tract, which is composed of the cavities of the head (nasal and mouth), filters the input. The placement of the articulators at any instant will determine the frequency of the sound produced, as filtered by the vocal tract. This complex time-variant filter network produces human speech.

To produce speech artifically requires an analog electrical signal that can approximate the human vocal process. Using filter oscillators, and noice generators this can be done fairly well. The complication is control of the static and dynamic parameters of speech.

Texas Instruments' SPEAK & SPELL learning aid uses a process based on a voice-compression technique called linear predictive coding (LPC). This technique can generate high quality speech at a low data rate -- less than 2400 bits per second. Linear predictive coding is so called because coefficients that characterize the digital filter may be predicted from a linear combination of the previous coefficients.

SPEAK & SPELL uses a modified calculator processor (TMC 0271) as its controller. This controller, a member of the TMS 1000 family, has been modified to enhance its binary-coded decimal arithmetic and expanded instruction set. The function of the controller is to pass data to the voice synthesis processor (VSP) and to the display, and to perform the number crunching mathematics required.

The VSP enables communication with the microprocessor and voice-memory. Speech data that has been compressed is supplied to the voice-processor either from the CPU or the voice-memory. The voice-processor decodes this data to produce a time-varying digital filter model of the vocal tract. This model is excited by a representation of either the glottal air impulse (voiced sounds) or the rush of air

(unvoiced sounds). The output of this model is passed through an eight-stage digital-to-analog converter to produce a synthetic speech waveform.

The voice synthesis memory (TMS 6100) stores the speech data as read-only memory. These ROM sets are 16,384 by 8-bit devices (128 Kbits) having an internal 18-bit address counter/register and two 8-bit output buffers. Fourteen of the address bits go to the memory array directly, while the four most significant bits are used in a 1 of 16 chip select. Data is fed serially out to the voice-processor using the ADD 8 line.


IMPLEMENTING SPEECH ON YOUR SYSTEM-50

By Tim McKee


This article discusses the hardware and software needed to interface a Texas Instruments' SPEAK & SPELL, which has been modified with a PERCOM SPEAK-2-ME-2 as discussed in Sam Campbell's article, to your 6800 computer.

There are two quick and easy ways to interface your speech unit using an M6821 parallel interface adapter (PIA). One, you can use a SWTP MP-LA card set for output on channel A and input on channel B, or, two, you can use a Percom 30-pin prototyping card with voltage regulation and a PIA, and work from there.

When you order a SPEAK-2-ME-2, you will be asked which of two cables you need. Either one works. The cable is shown in Figure 1.



Cut off the connector at the computer end. You do not need this connector for your System-50 computer. Separate the wires of the cable to about two inches. Strip about 1/4-inch of insulation from each wire. Position the cable assembly as shown in Figure 1. The wires numbers, from left to right, are #1 to #16. Cut off #11 and #15. Connect all of the even-numbered wires to ground. The remaining wires are connected as shown in Figure 2.



Speech driver programs are included at the end of this article. If space permits, we will include an *advanced* speech driver in the next issue of the Peripheral.

Listing # 1 is a position-independent driver for SPEAK-2-ME-2. It assumes the PIA is located at \$8000 (port 0. Prior to calling the driver, you must store the word value in VALUE, which is located at the starting address †9. The code could be reassembled to accept the value passed in the Index register, on the Stack, etc. You should do a 'JSR' to the starting address. The driver will speak the word, wait for it to finish, then return. The contents of VALUE are destroyed.

Listing # 2 is a BASIC program that will allow you to install the above driver and initialize the I/O port. There must be an area of memory inaccessible to BASIC and your DOS where the driver will be stored. This address must be given in line #170. The BASIC must have a USER function, which allows you to use machine language routines from BASIC. The address of the 16-bit value that allows you to

point the USER func anguage routine mus 200. Lines #330 and at \$8000. If your PIA i you must change these

			* * *
			*
(800 800 800 800	0) 1) 2)	P1 P1 P1 P1
0000 0002 0003 0005	30 EE 31 31	00	EI HI
0007 0009 000B 000D 000F 0011 0013 0015	00 A6 E5 A7 E7	02 00 07 08 08 07 07 0C 05	V
0019 001A 001C 001D 001F 0021	8D 5A 26 86	2F FA 80 28	RF
0023	4F		SF
0024 0025 0027 0029 002B 002D 002E	8D 4F C6 8D 8D 5A 26	25 05 37 18 F9	OU

point the USER function at your machine language routine must be specified in line #200. Lines #330 and #340 initialize the port at \$8000. If your PIA is at a different location, you must change these lines. Now, any word

in the SPEAK & SPELL vocabulary may be spoken. All that you must do is load variable A with the value of the word to be spoken and GOSUB 2000. AO must point to the first byte of the routine.

PERCOM 6800 ASSEMBLER

SPEECH DRIVER for 6800

- * THIS DRIVER IS AN ADAPTATION OF THAT WRITTEN BY
- * JAMES STUTSMAN FOR THE TRS-80 MODEL I.
- * THIS DRIVER IS WRITTEN IN POSITION INDEPENDENT 6800
- * CODE. IT REQUIRES THAT THE CALLING PROGRAM STORE
- * THE VALUE OF THE WORD TO BE SPOKEN IN THE VARIABLE
- * 'VALUE'. THIS VARIABLE IS DESTROYED BY THE ROUTINE.
- * WRITTEN BY TIM .MCKEE
- * COPYRIGHT PERCOM DATA CO. 1981

(8000) (8000) (8001) (8002) (8003)	PIA EQU PIADTA EQU PIACTA EQU PIADTB EQU PIACTB EQU	\$8000 PIA PIA+1 PIA+2 PIA+3
0000 8D 00 0002 30	ENTRY BSR	HERE
0003 EE 00 0005 31	HERE TSX LDX INS	0,X GET ADDRESS OF 'HERE'
0005 31	INS	FIX STACK
0007 20 02	BRA	*+4 SKIP AROUND VALUE
0009 00 00	VALUE FDB	0
000B A6 07 000D E5 08	LDA	A VALUE-HERE,X
000F A7 08	LDA	B VALUE-HERE+1,X
0011 E7 07	STA	A VALUE-HERE+1,X
0013 AA 07	ODY	B VALUE-HERE, X DRIVER REQUIRES REVERSED SEQUENCE
0015 26 OC	BNE	A VALUE-HERE,X OR THE TWO HALVES SPEAK SPEAK WORD IF NON-ZERO
0017 C5 05	LDA	
0019 4F	RESET CLR	
001A 8D 2F	BSR	STROBE SEND A ZERO
001C 5A	DEC	
001D 26 FA	ENE	RESET MUST SEND 5 TIMES
001F 85 80		A #\$80
0021 20 28	BRA	STROBE
	* THE FOLLO	VING CODE WILL 'SPEAK'
0023 4F	SPEAK CLR	
0024 8D 25	BSR	STROBE
0025 4F	CLR Z	
0027 C6 05	LDA I	3 #5
0029 8D 37	OUTADD BSR	SHFTX4 SHIFT LEAST SIGNIFICANT NIBBLE IN
002B 8D 18	BSR	OUTCHR SEND NIBBLE
002D 5A	DEC I	

OUTADD

DEC B

BNE

002D 5A

002E 26 F9

```
0030 86 80
                     LDA A #$80
0032 8D 17
                     BSR STROBE
0034 86 A0
                      LDA A #$A0
0036 8D 13
                     BSR
                          STROBE
0038 86 E0
                      LDA A #$EO
003A 8D OF
                      BSR
                            STROBE
003C 4F
                      CLR A
003D 8D 0C
                      BSR
                            STROBE
              * WAIT FOR COMPLETION OF WORD
003F B6 8002
              WAIT
                      LDA A PIADTB
                                      GET STATUS WORD
0042 2A FB
                      BPL
                            WAIT
0044 39
                     RTS
0045 36
              OUTCHR PSH A
0046 86 20
                      LDA A #$20
0048 8D 01
                      BSR
                            STROBE
004A 32
                     PUL A
004B 43
              STROBE COM A
004C B7 8000
                    STA A PIADTA
                                      PUT DATA ON LINES
004F B6 8001
                     LDA A PIACTA
                                      GET CONTROL CONTENTS
0052 84 F7
                     AND A #$F7
0054 B7 8001
                     STA A PIACTA
                                      SET STROBE LINE LOW
0057 8A 08
                     ORA A #8
0059 36
                     PSH A
005A 32
                     PUL A
005B 36
                     PSH A
005C 32
                     PUL A
005D 01
                     NOP
                                      THIS IS A DELAY SEQUENCE
005E B7 8001
                     STA A PIACTA
                                      STROBE LINE HIGH
0061 39
                     RTS
              * THIS ROUTINE WILL SHIFT THE LEAST SIGNIFICANT
              * NIBBLE (4 BITS) FROM 'VALUE' INTO ACC A.
0062 37
              SHFTX4 PSH B
0063 C6 04
                     LDA B #4
0065 8D 05
              SHFT4
                     BSR
                          SHFTR
                                      SHIFT ONCE
0067 5A
                     DEC B
0068 26 FB
                     BNE
                            SHFT4
                                      LOOP 4 TIMES
006A 33
                     PUL B
                                      RECOVER VALUE
006B 39
                     RTS
006C 67 07
              SHFTR ASR
                            VALUE-HERE, X SHIFT MOST SIGNIFICANT BYTE
006E 66 08
                            VALUE-HERE+1,X SHIFT LEAST SIGNIFICANT BYTE
                     ROR
0070 46
                     ROR A
                                     SHIFT INTO ACC A
0071 39
                     RTS
                     END
```

SPEECH DRIVER INSTALLER

0010	LINE= 0
0100	PRINT CHR\$ (26);: REM CLEAR SCREEN
0200	TRIMI CHRO (20); . REM CLEAR SCREEN
0110	REM YOU MUST SELECT AN AREA OF MEMORY INTO WHICH
0110	REM 100 MOSI SELECT AN AREA OF MEMORY INTO WHICH
0120	REM THE MACHINE LANGUAGE CODE FOR THE SPEECH DRIVER
0120	NEW THE MACHINE LANGUAGE CODE FOR THE SPEECH DRIVER
0120	DEM WILL DE DIAGED
0120	REM WILL BE PLACED. THIS AREA MUST REMAIN UNTOUCHED
0140	DEM DU DAGEG AND THE THE THE THE THE THE DESTRUCTION ON TOUCHED
0140	REM BY BASIC AND THE DOS/OPERATING SYSTEM. THIS
0150	Day of Brailing Biblish. This
0120	REM AREA MUST BE 114 BYTES LONG THIS DOCEDAM AND
0120	REM AREA MUST BE 114 BYTES LONG. THIS PROGRAM AND

0160 REM TH 0170 A0=430 0180 REM YO 0190 REM VE 0200 A9=99 0210 PRINT 0220 A=INT(0230 POKE (A 0240 A=A0-(0250 POKE (A 0260 FOR X= 0270 READ A 0280 POKE (A 0290 NEXT X 0300 PRINT 0330 POKE (3 0340 POKE (3 0350 REM IN 0360 REM IN 0370 A=USER 0380 A=1999 0390 PRINT 0400 PRINT 0410 PRINT 0430 READ A 0440 GOSUB 0450 END 1000 DATA 1 1010 DATA 2 1020 DATA 8 1030 DATA 5 1040 DATA 1 1050 DATA 5 1060 DATA 1 1070 DATA 1 1080 DATA 1 1090 DATA 1 1100 DATA 1 1110 DATA 8 1120 DATA 1 1130 DATA 3 1140 DATA 7 1800 DATA 1 1810 REM 18 2000 IF A<0 2010 POKE (2020 POKE (2030 A=USER 2040 RETURN

SBC/02 WORKS W PRO

By Ph

Programs written for the 6809 version following transfer add that the program doe calls other than the usulisted in Appendix D o

00

ERROR(S) DETECTED

```
0160 REM THE OTHER PROGRAMS ASSUMES A LOCATION OF $A800
0170 A0=43008 : REM REPLACE THIS VALUE WITH YOUR ADDRESS
0180 REM YOU MUST KNOW THE LOCATION THAT CONTAINS THE USER
0190 REM VECTOR.
0200 A9=99 : REM ADDRESS OF USER VECTOR FOR SUPER BASIC
0210 PRINT "INSTALLING BASIC SPEECH DRIVER, PLEASE STAND-BYE"
0220 A=INT(A0/256)
0230 POKE(A9,A) : REM INSTALL MSB OF USER VECTOR
0240 A=A0-(256*A)
0250 POKE(A9+1,A) : REM INSTALL LSB OF USER VECTOR
0260 FOR X=0 TO 113
0270 READ A
0280 POKE (A0+X,A)
0290 NEXT X
0300 PRINT
0330 POKE (32769,0) : POKE (32768,255) : POKE (32769,60)
0340 POKE(32771,0) : POKE(32770,0) : POKE(32771,60)
0350 REM INITIALIZE PIA A SIDE FOR ALL OUTPUTS, CA2 HIGH
0360 REM INITIALIZE PIA B SIDE FOR ALL INPUTS
0370 A=USER(0) : REM RESET S2M2
0380 A=19991 : GOSUB 2000
0390 PRINT
0400 PRINT "SPEECH DRIVER INSTALLED, PORT INITIALIZED."
0410 PRINT "READY FOR USE !"
0430 READ A : IF A=0 THEN 450
0440 GOSUB 2000 : GOTO 430
0450 END
1000 DATA 141,0,48,238,0,49,49,32
1010 DATA 2,0,0,166,7,230,8,167
1020 DATA 8,231,7,170,7,38,12,198
1030 DATA 5,79,141,47,90,38,250,134
1040 DATA 128,32,40,79,141,37,79,198
1050 DATA 5,141,55,141,24,90,38,249
1060 DATA 134,128,141,23,134,160,141,19
1070 DATA 134,224,141,15,79,141,12,182
1080 DATA 128,2,42,251,57,54,134,32
1090 DATA 141,1,50,67,183,128,0,182
1100 DATA 128,1,132,247,183,128,1,138
1110 DATA 8,54,50,54,50,1,183,128
1120 DATA 1,57,55,198,4,141,5,90
1130 DATA 38,251,51,57,103,7,102,8
1140 DATA 70,57
1800 DATA 19513,20492,9765,20492,-16631,0
1810 REM 1800 WILL SAY "READY TO TALK TO YOU"
2000 IF A<0 LET A=65536+A
2010 POKE ( A0+9, INT (A/256))
2020 POKE ( A0+10, A-256*INT (A/256))
2030 A=USER(0)
```

SBC/02 MONITOR WORKS WITH SWTBUG PROGRAMS

2040 RETURN

By Phil Sanders

Programs written for the SWTBUG monitor can be used with the SBC/02 monitor (monitor for the 6809 version of the SBC/9) with the following transfer addresses. This is provided that the program does not make subroutine calls other than the usual (INCH, OUTCH...) as listed in Appendix D of the LFD-400 or LFD-400

EX manual. Transfer addresses can reside in either RAM or ROM from \$E000 to \$E3FF. These addresses being filters can add or enhance SWTBUG compatible programs by jumping to a modifying subroutine before jumping to the SBC/02 monitor's vectors.


An LFD-400/800 controller card, decoded for \$E000-\$EFFF instead of \$C000-\$CFFF, was used for a PROM board. To decode the controller, to \$E000-\$EFFF, (1) cut the B10 pin 3 trace (to Address 13), (2) jumper from pin 40 of the Molex bus connector (Address 13) to A4 pin 13, and (3) jumper A4 pin 12 to B10 pin 3.

Percom PERIPHERAL

(ElAC)	ORG	SEIAC	
ElAC 7E FD33	JMP	\$FD33	INCH
210 /2 1200			
(E1D1)	ORG	SE1D1	
E1D1 7E FD26	JMP	\$FD26	OUTCH
BIDI /B IDEO	0	4	
(EOCC)	ORG	\$EOCC	
EOCC 7E FD9A	JMP	\$FD9A	OUTS
Bucc /B 123.1	0	4	
(E06B)	ORG	SE06B	
E06B 7E FD1C	JMP	SFD1C	OUTHR
1000 /1 1010	0		
(E0C8)	ORG	SEOC8	
E0C8 7E FD96	JMP	SFD96	OUT4HS
2000 12 1230	0	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
(E07E)	ORG	SE07E	
EOTE TE FD4B	JMP	SFD4B	PDATA1
2072 72 12.2	•		
(E0E3)	ORG	\$EOE3	
E0E3 7E FD65	JMP	SFC65	CONTRL
8083 /8 1203	0		
(E047)	ORG	\$E047	
E047 7E FDF8	JMP	SFCF8	BADDR
DOST TO IDEO	END	4-0-0	
	2112		

NEW PRODUCTS

We introduce new products for SYSTEM-50 computers several times a year. Our latest is a dual asynchronous serial communications interface module for the 30-pin bus. This SIO card packs more features per dollar than any we have seen.



Features:

Available with or without an optional on-card bit-rate generator (BRG). The BRG may be used to produce transmit/receive clock rates, thereby freeing up to five pins on the system bus for other use -- such as extended 1Mbyte addressing.

☆ Compatible with both the older and newer versions of the Systems-30 bus.

☆ Design permits control of serial-to-parallel and parallel-to-serial data conversion, parity generation and verification, and modem control -- with minimal software overhead.

☆ Output signals of each channel are current-limited for protection against a short-circuit load.

☆ Transmit and receive rate of each channel may be individually selected. Moveover, the transmit rate of a channel may be different from its receive rate. Data rate: 110, 300, 1200, 2400, 4800, 9600, and 19200 bits/second. ☆ Communications signals are compatible with RS-232-C standard levels. Clock signals are TTL compatible.

Low price: Only \$59.95 without the optional bit-rate generator, only \$74.95 with the BRG components installed. Field upgrade

BRG kit is only \$19.95.

Some thumbnail descriptions of some more new products are set forth below. These briefs were prepared by Dale French of our technical staff.

M24SS Static RAM Card: A 24-Kbyte static RAM board organized into three independent 8-Kbyte blocks. Works with either the standard SS-50 bus or the 1-Mbyte extended addressing bus. Comes assembled, burned-in and tested. Users manual includes source listing of diagnostic memory test. Also available in 8- and 16-Kbyte configurations.

M48DSS Dynamic RAM Card: A low power 48-Kbyte dynamic RAM board organized into three independent 16-Kbyte blocks. Works with either the standard SS-50 bus or the 1-Mbyte extended addressing bus. Comes assembled, burned-in and tested. Users manual includes source listing of diagnostic memory test. Also available in 16- and 32-Kbyte versions.

ColoRAMa-50: A memory-mapped color VDG board. Generates alphanumerics, semigraphic displays. Full graphic resolutions range from 64 x 64 pixels to 256 x 192 pixels. Displays in two, four or eight colors, depending on the display resolution. Twoand four-color displays may be complemented. Board is designed to accommodate a low cost Radio Shack modulator for TV set display. Comes with on Kbyte of display RAM which provides for alphanumeric, semigraphics and two low-density full graphic display formats. Also provides for 2-Kbyte EPROM. Cassette 1/0 provides for low-cost tile storage. Users manual includes source listing of display OS. Works with 1-Mbyte extended addressing bus. The ColoRAMa-50 occupies an 8-K-byte block of memory in the upper half of a 64-Kbyte address space. Board accommodates additional RAM for higher density display modes.

The COLOR CONNECTION: A cable/circuit card assembly which is used to adapt the 6809-based TRS-80 Color Computer to the SS-50 bus. The COLOR CONNECTION allows access to LFD-400 mini-disk storage, RAM

mnDOW, e.g.) to a visual display system, etc.

55-50 Bus Motherboard and for servicing funct.

55-30 Bus Motherboard to eight 30-pin complete with PC kromponents required for the property of the property of

Exorciser C Prod

Motorola's EXORC dustrial quality 680X r 86-pin system deplated edge type of the color of the co

ROUTINE	MIK	M
INCH	ElAC	F
OUTCH	ElDl	F
OUTS	EOCC	F
OUTHR	E06B	F
OUT 4HS	EOC8	F
PDATA1	E07E	F
CONTRL	E0E3	F
BADDR	E047	F
1/0		
TYPE	PIA	A
ADDRESS	8004	8

A supplement to this is available from Percon supplement includes m—for example, notes o and maintenance -- an price list. This s automatically mailed Peripheral, may be obcalling our toll-free or 1592. From within Te:

expansion, interfacing (via the ELECTRIC WINDOW, e.g.) to a word-processing quality BW display system, etc.

SS-50 Bus Motherboard: A seven-slot system bus card that can also be used as an extender card for servicing function cards.

ss-30 Bus Motherboard Kit: Accommodates up to eight 30-pin I/O cards. Supplied complete with PC board connectors and components required for application as an I/O

extension motherboard for the SS-50 bus.

Since the last Peripheral was issued, many new 680X programs have been released, including MPX/9, a 6809 DOS for our LFD disk systems, and a 6809 version of Percom Super BASIC.

To place an order or request product literature, call our toll-free order number, 1-800-527-1592. For additional technical information call (214) 272-3421.

Exorciser Compatible Products

Motorola's EXORciser is a versatile, industrial quality 680X microcomputer. It uses an 86-pin system bus, with standard gold-plated edge type connectors for function cards. Our EXORciser compatible boards, called ModulEX modules, are equal in quality to Motorola modules but cost far less. Included in this product line is the LFD-400/800 EX mini-disk system; a VC-EX memory-mapped video display card; and, the M64EX, a 64-Kbyte dynamic RAM card. A 6809 MPU card is in the board-layout stage of development. Software for these systems include a number of monitors -- MIKBUG,

EXBUG and others -- configured for LFD-400/800 EX operation, Percom Super BASIC, an editor and business application programs.

I/O subroutine entry addresses for EXBUG 1.1, EXBUG 1.2 and CRTBUG, plus an entry address for the MINIBUG III CONTRL subroutine have been established. These are set forth in the table below, and are to be added as an extension to Appendix D of the LFD-400/800EX Users Manual. We will soon release similar entry addresses for D3BUG1, D3BUG2, and MIKBUG 2.0. If you are interested in using the LFD-400/800EX with one of these monitors, or if you have a monitor that is not listed in Appendix D of the Users Manual, contact Percom.

ROUTINE	MIK BUG	MICRO BUG	MINI BUG II	MINI BUG III	TVBUG	EXBUG 1.1	EXBUG 1.2	EXBUG 2.1	SYS MON CMS	CRTBUG
INCH OUTCH OUTS OUTHR OUT4HS PDATA1 CONTRL BADDR	E1AC E1D1 E0CC E06B E0C8 E07E E0E3 E047	FD33 FD26 FD9A FD1C FD96 FD4B FC65 FCF8	E11F E108 E180 E0FE E07C E130 E040 E0D9	E133 E126 E19A E11C E196 E14B E065 E0F8	F800 F803 F9B4 F986 F80F F806 F821 F809	F015 F018 F02A FA1C F01E F027 F564 F00F	F015 F018 F02A FA0F F01E F027 F564 F00F	F015 F018 F02A F0D0 F01E F027 F564 F00F	F9D1 F9E8 F8EB F881 F8E7 F894 F81C F864	E508 E494 E427 F3C8 F423 E3D9 E09B E3A4
I/O TYPE ADDRESS	PIA 8004	ACIA 8408	ACIA 8008	ACIA 8008	PIA F404	ACIA FCF4	ACIA FCF4	ACIA FCF4	ACIA E3C0	ACIA/PIA 8008/8044

A supplement to this issue of the **Peripheral** is available from Percom Data Company. The supplement includes more specific information --for example, notes on product improvement and maintenance -- and a 'short-form' product price list. This supplement, which is automatically mailed to subscribers of the **Peripheral**, may be obtained from Percom by calling our toll-free order number, 1-800-527-1592. From within Texas, call (214) 272-3421.


TRADEMARKS APPEARING IN THIS ISSUE OF THE PERIPHERAL:

Percom Data Company, Inc.: ColoRAMa-50, the COLOR CONNECTION, ELECTRIC CRAY-ON, ELECTRIC WINDOW, EXDOS, INDEX, LFD-400, LFD-800, ModulEX, MPX/9, PSYMON and SBC/9.

Motorola Corp.: EXBUG, EXORciser, MICROBUG, MICRO CHROMA, MIKBUG and MINIBUG.

Tandy Radio Shack Corp.: TRS-80
Microware® Systems Corporation: OS-9
Technical Systems Consultants, Inc.: FLEX,
FLEX/9, UNIFLEX

Now! Color for Your...



Introducing COLORAMA-50[™] Percom's SS-50 Bus Color VDG

Featuring ...

 Eleven display formats including 8-color semigraphics, 4color graphics, 2-color high density graphics and 2-color alphanumerics.

Moreover, two- and four-color displays may be switched between primary and complementary color sets under software control or from the keyboard.

Full graphic resolutions range from $64\,x\,64$ picture elements to $256\,x\,192$ picture elements.

 Instant display control: The COLORAMA-50™ is memory mapped: your MPU has direct, instant access to display RAM and display control registers.

• Low-cost Modulator Option for Color TV Interface: The COLORAMA-50™ provides for installation of an inexpensive RF modulator such as Radio Shack PN 277-122 for operation using a color TV.



SS-50 Bus Department Store

Nobody supports the SS-50 bus like Percom:

- SS-50 Bus/Single-Board Computers with I/O ports & memory
- Static and Dynamic RAM cards memory expansion kits
- LFD-400/800 1-, 2- and 3-drive mini-disk systems
 Color and monochrome memory-mapped display controllers
- ✓ Extendable 7-slot SS-50 bus motherboards
 ✓ Versatile prototyping boards: SS-50 and SS-30 bus
 ✓ Field-proven software: monitors, operating systems, drivers, editors, assemblers, debuggers and HLLs.

Mix in Sound: With the optional modulator installed, you can complement your colorful displays with software-controlled audio.



- Extended Addressing: The COLORAMA-50™ is compatible
 with the SS-5CA bus and the extended-address SS-5OC bus.
 Map the board into any of the sixteen 64-Kbyte banks of the
 1-Mbyte SS-5OC address space. The COLORAMA-50™ card
 "defaults" to the first (lowest) bank for the SS-50A bus.
- Cassettee I/O Option: Add a few inexpensive components to the on-card circuitry provided and use an audio cassette for program/data storage.
- Provision for On-Card Firmware: Put your display operating system, cassette control program, etc. right on the COLORA-MA-50™ card in a 2516 (5-volt 2716) EPROM. Resides in the top 2-Kbyte of the card memory space.
- Operating Software: Included in the comprehensive users manual is a listing of a display operating system and cassette controller that may be implemented as a callable subroutine function from BASIC or existing operating systems. The programs are optionally available in a plug-in ROM for just \$69.95.

System Requirements

The COLORAMA-50™ is pin- and outline-compatible with the Percom System-50™ bus, the SS-50A (SS-50) bus and the SS-50C bus. The composite video-sync signal output will directly drive a color (or BW) video monitor. The output may be modulated for operation with a standard (NTSC) TV set. A modulator is not included. The COLORAMA-50™ card occupies 8-Kbytes of memory in the upper half of a 64-Kbyte memory space. Included on-card is 1-Kbyte of display RAM which will accommodate alphanumeric displays, semigraphic displays and two low-density full-graphic displays. For the higher density graphic displays, additional display RAM is required. The optional RAM ICs may be installed on the card.

PERCOM DATA COMPANY, INC 211 N KIRBY GARLAND TEXAS 75042 (214) 272-3421



For quality Percom SS-50 bus products, see your nearby authorized Percom dealer. To order direct, call **toll-free**, **1-800-527-1592**. Prices and specifications subject to change without notice. Prices do not include shipping and handling.

PERIP

OUR NEWEST 1

16K Kit plus

32K Expansion modify it for the extra modify

WE ARE WELL. BUS.

FD-1: Use Also

FD-1B: Bare

FD-S2: Cont

FD-S1: Con

cab:

1771-1 Flor

COLOR GRAPHI

VDG-1: 10 n 256 ASSI

TERMS:

COL

Alsc

TM trademark of Percom Data Company, Inc.

PERIPHERAL TECHNOLOGY

OUR NEWEST PRODUCTS FEATURE MEMORY EXPANSION FOR THE TRS-80C.

16K Kit plus instructions

\$ 34.95

32K Expansion: Send us your TRS-80C. We will modify it for 32K. Basic automatically uses the extra memory. Send for details.

\$109.95

WE ARE WELL-KNOWN FOR OUR FLOPPY DISK PRODUCTS FOR THE S-50 BUS.

FD-1: Use with SWTPC 6800. Also available in kit form. \$ 99.95

FD-1B: Bare board + documentation. ONLY \$ 27.00

FD-S2: Controller, cables, power supply,

cabinet, dual drives

\$799.95

FD-S1: Controller, cables, power supply,

cabinet, single drive \$459.99

\$459.99

1771-1 Floppy disk controlller chip

\$ 24.00

COLOR GRAPHICS - OUR BOARD CAN PERFORM ALMOST ANY GRAPHICS FUNCTION.

VDG-1: 10 modes of operation. 32 x 16 alphanumerics to 256 x 192 graphics. 6K RAM.

ASSEMBLED AND TESTED:

\$225.00

Also available with 1K RAM.

INFORMATION AVAILABLE FROM:

Peripheral Technology 290 Lamplighter Lane Marietta, Georgia 30067

TERMS: COD CHECK VISA MASTER CHARGE

404/953-3434

COMPUTER SYSTEMS CONSULTANTS, INC.

1454 Latta Lane, Conyers, GA. 30207 Telephone 404-483-1717 or 483-4570

SOFTWARE DEPARTMENT

(ALL PROGRAMS PROVIDED IN SOURCE ON DISK SPECIFY 5"/8")

ж		
	SUPER SLEUTH Disassembler System (for FLEX* systems) —runs on 6800/1/9, analyzes 6800/1/5/9 and 6502 —easy to use, self-instructive, with 42-page manual —automatic labels, optional FCB, FCC, FDBs —input binary file from disk or from memory —memory changes to program thru full-screen editor —output disk file may be source or new binary file —commands from menu or from and to disk file —generates FLEX* and user-defined names —includes assembler language XREF program —contact SMOKE or CER-COMP for non-FLEX* systems	\$ 99.0
	Z-80/8080/8085 Disassembler (Similar to SLEUTH) —runs on 6800/1/9, analyzes Z-80/8080/8085	\$ 99.00

6800/1,6805, 6502,Z-80,8080/5 Cross-assemblers —macro sets for TSC 6809 Macro Assembler

FULL-SCREEN FORMS DISPLAY for TSC 6809 X-BASIC
—display and edit for terminals and video displays
—complete cursor control for screen input/output

-interactive forms generator/documentor provided

FULL SCREEN MAILING LIST System for TSC 6809 X-BASIC —full screen update and selection to print or labels	\$ 100.00
TABULA RASA Tabular Calculation Program (COMING SOON) —similar to VISICALC (T.M. Personal Software)	\$100.00
TSC BASIC Resequencing and XREF Programs —processes TSC BASIC, X-BASIC, PC, XPC programs —partial and blank-resequence capabilities —alphabetized xref of all variables and BASIC verbs	\$ 25.00
TSC X-BASIC DISK SORT/MERGE Generator —generates TSC XPC BASIC sort/merge programs	\$ 25.00

HARDWARE DEPARTMENT

(ALL BOARDS BARE WITH FULL DOCUMENTATION PROVIDED)

-ASCII (TTL or RS-232+CTS) in, 26-50v solenoids out -2708 PROM with Correspondence ball codes	
SS-50 WIRE-WRAP BOARD (52-16 pin equivalent)	


SS-50 WIRE-WRAP BOARD (52-16 pin equivalent) SS-30 WIRE-WRAP BOARD (32-16 pin equivalent) SS-30 ACIA BOARD (all modem control lines) SS-30 DUAL ACIA BOARD (modem control + Baud rate gen)	\$ 25.00 \$ 15.00 \$ 15.00
SS-50 PRONT PANEL DISPLAY BOARD (16 decoded LED's)	\$ 30.00 \$ 10.00

VISA and MASTER CARD preferred: account, exp date, phone no. US funds only: Add 7.5% (15% Foreign) for postage & handling. For Catalog or dealer discount information contact Bud Pass

\$ 50.00 \$100.00

* FLEX is a trademark of Technical Systems Consultants

Model 6800CL4T CalClock/TIMER



IT'S A HARDWARE CALENDAR/CLOCK

- Keeps date and time without servicing by the computer
 Peruntangan mansh/day/year housemin-sec (12/24hr + auto-
- Day-of-week, month/day/year, hour:min:sec (12/24hr.+auto Leap Year)
 Hands off setting/control/access of ALL functions via software
- On-card battery and charging circuit keeps time for months, power off

WITH AN INTERVAL TIMER INCLUDED

• For (TSC/Flex 2/9 compatible) printer spooling, multi-tasking, etc.

Fully assembled & tested* Complete kit* Bare board*	\$ 99.95 \$ 69.95 \$ 35.00	5"Disk (Flex2□ Flex9□) [©] Goldplated buss connectors Shipping & handling	\$ 10,00 \$ 6,00 \$ 3.00	0

* FULLY DOCUMENTED: instructions; diagrams; theory; more than 20 pages of sample software (automatically puts date in Flex2/9 date buffer, adds time-of-day to assembly listings, maintains constant, current time-thate display on top line of CRT). Batteries not included. All IC's socketed.

© FLEX is the registered trademark of Technical Systems Consultants, Inc.



COMPUWARE Corporation P.O. Box 2710 Cherry Hill, NJ 08003 609-428-2309 Dealer & Volume Discounts

New Jersey buyers: ADD 5% Terms: CASH; MC; or Visa Flex9[®]□ Flex2[®](default)□



Utility Disk 1

FEATURING:

[1] BASASM V2 A BASIC "Assembler"

[2] DDISSEM

\$ 35.00

\$ 15.00

\$15.00

(with source)

A Disk Disassembler Disassembles directly from the disk.

[3] SDCOPY

A Single-Disk Copy

Available on 5¼ inch FLEX 2.0 disk. ('09 versions of #1 and 3 included)

Send cash, check, money order or charge it on VISA or MC. [No COD's]

SS-50 Computing

P.O. Box 398

Garland, Utah 84312

MEMO

- * USES LOW COST 4116
- * TOTAL TRANSPARENT R
- * LOW POWER CONSUMPTI
- * ADDRESSABLE IN 8-K
- * CAN BE USED WITH 16
- * EXTENDED ADDRESSING
- * OPERATES ON SS-50 A
- * SOLDER MASK AND SIL
- * ALL MEMORY CHIPS AR
- * KITS AND BOARDS ARE

SER

- * TWO ON BOARD DB-2
- * HAS ON BOARD BAUD
- * BAUD RATE MAY BE
- * BOARD CAN USE EXT
- * BAUD RATE IS PROG
- * FOR THE SS-30 BUS
- * ALL LINES BUFFERE
- * ALL REGULATORS 1

CABLE

- * RS-232 8. ft.
- * RS-232 EXT. 4,6t.
- * RS-232 EXT. 4,6t.
- * 5% dual drive 10ft
- * 8"dual drive 106t
- * 8"auae areve 1082
- * 8"dual (SSB) 106t

SOUTHERSTERN MICRO SYSTEMS inc.

DM-64

MEMORY BOARD

- * USES LOW COST 4116 DYNAMIC RAM
- * TOTAL TRANSPARENT REFRESH: OPERATES LIKE STATIC
- * LOW POWER CONSUMPTION 64-K Assembled \$429.00
- * ADDRESSABLE IN 8-K BLOCKS
- * CAN BE USED WITH 16K to 64K
- * EXTENDED ADDRESSING TO 16 BOARDS 16K Kit
- * OPERATES ON SS-50 AND SS-50C BUSS \$249.00
- * SOLDER MASK AND SILKSCREENED BOARDS
- * ALL MEMORY CHIPS ARE PRIME 4116-200ns
- * KITS AND BOARDS ARE IN STOCK

DS-16

SERIAL INTERFACE

- * TWO ACIA PORTS
- * TWO ON BOARD DB-25 CONNECTORS (on top of board)
- * HAS ON BOARD BAUD RATE GEN
- * BAUD RATE MAY BE PROGRAMMED FOR ON OR OFF BOARD USE
- * BOARD CAN USE EXTERNAL BAUD RATE FROM BUSS OR RS-232
- * BAUD RATE IS PROGRAMMABLE TO 32K-baud

- * FOR THE SS-30 BUSS
- \$119.88 * ALL LINES BUFFERED Assembled
- * ALL REGULATORS 1 amp. +5 +12 -12

DISKS & Accessories _____

*	WABA	SH IBO	ox Price)	
*			OS/DD, soft sector	\$42.10
*		51/4"	SS/SD, HARD	27.60
*		5%"	DS/DD, soft Sector	37.70
*		514"	DS/DD, HARD	37.70
*				
*	3M 8	DATA	LIFE (Box Price)	
*	-	5411	SS/SD or SS/DD	\$37.50

54" DS/DD on DS/SD 8" SS/SD or SS/DD 40.00 8" DS/DD on DS/SD 55.00

\$25.95 * Head Cleaning Diskette Kits (54" or 8")

* Plastic Library Case 3.50

CABINETS

Dual Mini Disk Enclosure \$49.00 Cabinet with Hardware 59.00 (Includes Power Cord Fuse Holder, Switches, Mounting Screws)

CRYSTALS

*	1.000 MHZ	\$4.95
*	1.84320 MHZ	4.95
*	4.000 MHZ	3.50
*	15.3600 MHZ	5.95
	1313000 14112	3.73

BTR-09

TERMINATOR BOARD

CABLES

- * RS-232 8, ft. \$24.00
- * RS-232 EXT. 4.6t. 19.50
- * RS-232 EXT. 4,6t. 24.00
- * 5% dual drive 10ft 35.00
- * 8"dual drive 10ft 45.00
- * 8"dual (SSB) 10ft 47.00 ********


- * FOR SS-50 and SS-50C BUSS
- Assembled
- * WILL REMOVE MOST ADDRESS AND DATA LINE NOISES
- * SYSTEMS RUN WITH LESS ERRORS
- * DISK SYSTEMS PERFORM BETTER



SEND YOUR ORDER TO

1080 IRIS DR P.O. BOX 293 CONYERS, GA. 30207

ADD \$5.50 FOR SHIPPING IN USA \$10.50 FOREIGN (US FUNDS ONLY)



ADVENTURE GAMES

ComputerwareTM will distribute the Mark Data Products adventure games on SSB DOS.

Calixto Island Adventure \$24.95

Check Ledger System

\$199.95

Single entry bookkeeper for income & expenses through your check ledger — many sorts & reports (Reg. \$399.95)

Correspondence System

\$149.95

Comprehensive mailing list system with special codes & selective sorts (Reg. \$249.95)

Random Data Organizer

\$79.95

Flexible data file manager with disk lister for directory sorts & reports

Basic Finance

\$34.95

Loans, investments, depreciation, income property

- 6809 Disk Utilities \$34.95
- Think Games \$29.95
- 6800 Disk Utilities \$29.95
- MANY MORE

All products require current SSB DOS & Random BASIC (6800 or 6809)

COMPUTERWARE"

1472 Encinitas Blvd. • Box 668 Encinitas, CA 92024 • (714) 436-3512

TO ORDER

Phone orders invited. Use VISA, Master Charge or send money order drawn on a U.S. bank. Add 2% shipping charge. Minimum \$2.00 shipping.

6809 DATAI

*USER DEFINED RECORD FOR *SCREEN ORIENTED, FORM F *OPTIONAL TWO LEVEL RECO *ALL FILES IN ASCII TEXT FO *DIRECT ACCESS BY KEY FIE *EXTENSIVE DOCUMENTATIO *VERSATILE, PROFESSIONAL *BUILT-IN SORT/MERGE *EASY TO USE



The BEST 6800 mon friendliness and simp HUMBUG-09 probut adds full trace an keep track of multiple You can switch I/O povideo boards, even processing the second se

It has a very sim Adding non-standard automatic. Makes the

Most important, I exactly what you expe with 6800 HUMBUG

The initial versior RAM; it does not s video-based versions commented source li

And here's an of trade-in credit when a issue for our other fir

S


6809

RECORD MANAGEMENT SYSTEM

RMS

DATABASE MANAGEMENT

- •USER DEFINED RECORD FORMAT VIA DATA DICTIONARY
- •SCREEN ORIENTED, FORM FILL OUT TYPE OF ACCESS
- OPTIONAL TWO LEVEL RECORD HIERARCHY
- •ALL FILES IN ASCII TEXT FORMAT, BASIC COMPATIBLE
- •DIRECT ACCESS BY KEY FIELD, MULTIPLE INDEX FILES
- **•EXTENSIVE DOCUMENTATION, SAMPLE APPLICATION**
- •VERSATILE, PROFESSIONAL QUALITY REPORT WRITER
- •BUILT-IN SORT/MERGE
- **•EASY TO USE**



RMS is a complete DATABASE MANAGEMENT package for the 6809 computer. It is made up of five machine language programs that make up the most powerful business programming tool available for the 6809. It can be used by the relative novice, to implement an incredible variety of information storage and retrieval applications, without any programming. However, the programmer can use RMS as part of the solution to a larger problem, saving many hours of unnecessary program development time. RMS can be used to handle data input, editing, validation, on-line retrieval, sorting and printed reports. Custom data manipulation can be filled in by the user's BASIC programs.

SINGLE CPU LICENSE

FLEX* \$200 OS-9+ \$250 UNIFLEX* \$300

TERMS: VISA / MC / PREPAID

WASHINGTON COMPUTER SERVICES

3028 SILVERN LANE BELLINGHAM, WA 98225 1 (206) 734-8248

* FLEX and UNIFLEX are trademarks of Technical System Consultants Inc.; + OS-9 is a trademark of Microware

6809 HUMBUG!

The BEST 6800 monitor is now available for the 6809. Get the power of a 6809, but keep the friendliness and simplicity of the 6800 with HUMBUG-09.

HUMBUG-09 provides the common functions and commands of your present monitor, but adds full trace and debugging facilities. With it you can single-step programs, insert and keep track of multiple breakpoints, dump memory, abort and continue programs, and more. You can switch I/O ports during execution of a program, link to user-supplied I/O routines or video boards, even pause when the screen is full.

It has a very simple — yet new — way of handling the DAT that eliminates all hassles. Adding non-standard equipment such as disk controllers or video boards is easy and automatic. Makes the DAT work for you instead of against you.

Most important, HUMBUG-09 takes the mystery out of your 6809 system. It always does exactly what you expect it to — no unpleasant surprises. It's based on a year's user experience with 6800 HUMBUG.


The initial version is for systems using the SWTP MP-09 CPU board and less than 64K of RAM; it does not support the DMF-2 disk. (Alternate versions available, including video-based versions). The price of \$75 includes two ROMs, complete manual, and either full, commented source listing or source code on disk — you choose!

And here's an offer you can't refuse: If you buy our 6800 HUMBUG, we'll give you full trade-in credit when and if you decide to upgrade to HUMBUG-09. See our ad in last month's issue for our other fine 6800/6809 products, or send sease For information.

STAR-KITS, P.O. Box 209, Mt. Kisco NY 10549

It's available

D64KB - 64K Dynamic Memory Board



For The SS-50/SS-50C Bus

- Completely TRANSPARENT Refresh [During 01] at 1 MHz
- Operates with BOTH 6800 and 6809 systems
- Compatible with the 20 bit extended addressing mode.
- Diode Protection On The -5V Power Line
- Memory Selection and Relocation For Testing
- LOW POWER 12V at 150 mA 5V at 500 mA -5V at 7 mA
- 4116 Type RAM With 200 ns Access Time
- Printed Circuit Board:
 Double Sided With Plated-Through Holes
 Silkscreen Component Layout On Top Side
 Solder Mask On Bottom Side
 9 inches by 5.8 inches
- Designed around Motorola MC3242A and MC3480 Delay Lines To Ensure:
- NO Timing or Temperature Problems
- NO [NONE] One-Shots
- NO Adjustments

PRICES

OPTION 1 - \$60.00 Includes PC Board and 18 Pages of Documentation.

OPTION 2 - \$80.00 Same as Option 1 plus Delay Lines

OPTION 3 - \$100.00 Same as Option 2 Plus the Two Memory Contollers

OPTION 4 - \$190.00 Same as option 3 Plus all other TTL chips [Full Kit, less memory]

OPTION 5 - \$230.00 Completely Assembled and Tested but Without 4116's

BOAZ Co. Box 18081 San Jose, Ca. 95158 Also available - Extender Boards from BOAZ

50 Pin Board - \$15.00 30 Pin Board - \$12.00

Orders Should Include \$5.00 Shipping California residents add 6 1/2% Sales Tax Cash - Check - Money Order

Allow 3-4 weeks for personal checks to clear.



- Convert y
- Automatic
- Allows sp
- Constants
- Automatic
- DISK-to-I Includes 5 object code minutes!)

Only \$60.00 6809, F order from: COM

we also

FLEX is a

DYNAMITE TM "THE CODE BUSTER" DISASSEMBLES 6800 & 6809 MACHINE CODE INTO BEAUTIFUL SOURCE

- Convert your 6800 programs to 6809!
- Automatic LABEL generation
- Allows specifying FCB's, FCC's, FDB's, etc.
- Constants input from DISK or CONSOLE
- Automatically uses system variable NAMES
- DISK-to-DISK or DISK-to-CONSOLE operation Includes 5" or 8" FLEX 9 diskette with relocatable object code. Full operating instructions (you'll learn in minutes!)

Order your DYNAMITE[®] today
Only \$60.00 postpaid in U.S. MC & VISA accepted
6809, FLEX 9, and 24K total RAM required
order from:

COMPUTER SYSTEMS CENTER

13461 Olive Blvd. Chesterfield, MO 63017 (314) 576-5020



we also stock SWTPC, TSC, JPC products

Dealer inquiries welcome FLEX is a trademark of TSC (Bless their hearts)

NOW AVAILABLE

 Accts. Receivable/Order Input.
 \$295.00

 Accts. Payable/Purchase Order
 \$295.00

 General Ledger
 \$295.00

 Manufacturer's Inventory
 \$295.00

 Payroll
 \$295.00

 Forms Supplier Package
 \$1195.00

 Foundry Package
 \$1195.00

 Manuals with Print-Outs
 \$ 20.00

DBM 1 FLEX*\$150.

DBM 2 FLEX*\$350.

UNIFLEX* \$450.

DBM 2 and DBM UNIFLEX contain source listings.

This is a comprehensive group of programs that allows a virtually *untrained* person the ability to store and recall vast amounts of information in a computer system to meet their individual requirements.

The user is guided through these extensive programs by *Menus* and *Sub-Menus*. By simply answering prompts, the user can create files, sort any type of data and recall or manipulate it at will. The size of the files is only limited by the disk storage capacity of the system.

Sub records of related information can contain as many as 27 different fields of information and can contain either alphanumeric, integer or floating point data.

The software is written in *TSC Extended Disk Basic utilizing well commented structured programming techniques. Custom Programs can be created quickly through the sub-routine library.

*FLEX AND UNIFLEX ARE TRADEMARKS OF TECHNICAL SYSTEMS CONSULTANTS.

2457 Wehrle Drive • Buffalo, New York 14221 • (716) 631-3011



TH THE MACHINE 1

NEW PRO

Special introductory

*Both cards assembled w SS-30 WIRE-WRAP/PROTU *Pad spacing permits mo *Provision has been made

FEA

special parts kit
A/T without extra feature
A/T with extra feature
A/T with extra features
Software obj. & src. on FI
SUPER CPU assembled
without 2K EPROMS (2Monitor in two 2708 EPROMS

MODEM CARD

All Thomas Instrumentation's assembled cards are burned in See previous ads, write, or ca

CONT. U

To satisfy in-depth questions rega

THOMAS INSTRUMENTATION

THE MACHINE TOOL, INDUSTRIAL SPECIALISTS IN BUSINESS ON A FULL TIME BASIS FOR 10 YEARS

NEW PRODUCT:

S-R/R

48K 2MHz STATIC RAM/ROM CARD

*24 2K blocks memory mapped on any 2K boundary

*uses low power 2016P-2 (2128) RAM and/or 2716 ROM

*mix 4K blocks of RAM and ROM

*6800 and 6809 compatible

*use on SS-50 and SS-50C buss

*decoded for extended addressing

*5 volts only

*low power consumption (typ. ½ amp with 48K RAM)

*gold connectors

Special introductory prices for all orders placed before July 1, 1981 — Regular price will be 20% higher.

Bare board \$39.20

2716 \$12.80

2016P-2 \$13.60

A/T without memory chips \$100.00

A/T with 16K \$220.00; with 32K \$316.00; with 48K \$440.00

NEW ACCESSORIES FOR 68XX USERS:

SS-50/SS-50C EXTENDER CARD

\$35.00

SS-30 EXTENDER CARD

*TRANSITION CARD bare

\$25.00

*Both cards assembled with a built in logic aid & gold edge connectors

SS-30 WIRE-WRAP/PROTOTYPE BOARD (board only)

\$20.00

80.00 60.00 40.00 30.00 20.00

*Pad spacing permits most standard sockets from 8 to 64 pins

*Provision has been made for voltage regulators

FEATURED PRODUCT:

SP-1 Bare card \$49.00 Asm. + tested \$195.00

*A super prototype board *Card design includes

(3) 6821 6 parallel ports

(4) 6850 4 serial ports

(1) 6840 3 16 bit counter/timers

which are fully buffered and decoded

*Accomodates a mix of 38, 14 & 16 pin wire wrap sockets
*Pad spacing permits most standard sockets from 8 to 64 pins

MODEM CARD	B/C	\$ 49.00	
speccial parts kit		\$195.00	BACKPLANES AND MOTHERBOARDS
A/T without extra features		\$325.00	*16 position SS-50
A/T with extra features		\$395.00	*12 position SS-50
Software obj. & src. on FLE	X disk	\$10.00	* 8 position SS-50
*SUPER CPU assembled			* 6position SS-50
			* 4 position SS-50
without 2K EPROMS (2-27		\$235.00	* 8 position SS-30
*Monitor in two 2708 EPROI	MS	\$ 29.00	o position oo oo
*CPU bare card, doc, & src.		\$ 59.00	**Connectors:
*VIDEO RAM asm. 7x9 chars		\$195.00	GOLD \$1.60 ea. (M or F)
*Video RAM bare, doc, Xtal,	src.	\$ 49.00	TIN M \$.40 ea. F \$.50 ea.
*PARALLEL I/O asm 100 I/O	O lines		1114 141 ф.40 са. г ф.50 са.
incl. 5 PIA'S for 10 ports		\$139.00	
*PARALLEL I/O bare card &		\$ 49.00	
*SS-50 WIRE-WRAP/PROTO	TYPE bare	\$ 39.00	
*TRANSITION CARD asm.		\$ 95.00	

\$ 49.00

DEALERS FOR SWIPC, GIMIX, AND TSC

THOMAS INSTRUMENTATION

168 EIGHTH STREET — AVALON, N.J. 08202 (609) 967-4280

NJ RES. INCLUDE 5% SALES TAX

CONT. USA INCLUDE \$3.00 SHIPPING, CANADA \$6.00, FOREIGN \$12.00

MASTERCARD, VISA, and C.O.D. ACCEPTED

To satisfy in-depth questions regarding our products send \$20.00 to receive full documentation, schematics, & source listings for all boards currently in production

^{*}All Thomas Instrumentation's cards come with full documentation including software source listings where applicable *All assembled cards are burned in at 150F and fully tested with Gold conn. *Bare card prices do not include edge connectors *See previous ads, write, or call for more detailed information.

STAR-KITS

6800 HARDWARE

SBC-02 single board computer uses 6802 with RAM, ROM, I O. Ideal controller, intelligent interface, and more. Printed circuit board is \$25, complete controller kit \$75, wired and tested \$150. Also available: HUMBUG (see below), Basic in ROM, etc.

CT-PS serial parallel interface card. ACIA-type interface for RS-232C terminal and or a parallel keyboard. Makes keyboard look like a terminal with absolutely no program patching. Ideal for video board based systems. Bare board \$20, complete kit \$55, wired \$100.

6800 FIRMWARE

HUMBUG monitor. Totally MIKBUG compatible, plus single-stepping, multiple breakpoints, formatted memory dumps, multiple port control and more. "Fantastic!" say our customers. 2K version \$40 on 2708 or 2716 EPROM with source listing. Alternate versions, including video board versions available.

PERCOM DOS PATCH gives more disk space, bigger directory. Best of all, adds error detection correction to your system so your files are guaranteed right. We correct your 2708s for \$40, or supply three new ones for \$50.

6800 SOFTWARE

BASIC UTILITY PACKAGE renumbers, pretty-prints, prints variable and transfer indexes, compares, shortens Basic programs. On Percom or miniFlex* disk for \$30.

CHECK 'N TAX balances your checkbook, finds errors, prepares income tax data. On Percom, miniFlex*, Flex 2 0* or Flex 9* disk for \$40.

 $\begin{array}{l} \textbf{SORT-MERGE} - \text{the only one for Percom disk systems,} \\ \text{sorts even full-disk files. } \$35 \end{array}$

BASTRAN a Basic preprocessor Adds long variable names, line labels instead of line numbers, and other conveniences to any standard 6800 disk Basic. On miniFlex* or Flex 2.0* disk for \$30.

6800 CROSS-ASSEMBLER written in Basic. Assemble 6800/6802 programs on your new 6809 (or your 370 at work!). Available on 5" disk, KC cassette, or TRS-80 Level II cassette for \$9.95.

GAME PACK with Eliza and 3-D Tic-Tac-Toe. 5 " disk or KC cassette \$15.

Send sase for catalog or more information. *are trademarks of TSC.

STAR-KITS, P.O. Box 209, Mt. Kisco NY 10549

SS-50 Bookstore

6809 Assembly Language Programming
This book presents a thorough introduction to assembly language programming and a complete discussion of
the 6809 instruction set. It starts at a
very basic level and builds into actual
programming techniques, I/O structures, and hardware interfaces. By
Lance Leventhal. 530 pages. Order
No. 357 \$16.99

6809 Microcomputer Programming and Interfacing/Experiments

This book is written to give sound information on how to program and interface the 6809-the high performance 8-bit microprocessor. It contains seven chapters and four appendices and is valuable as a "cookbook" aid when working with the 6809. By Andrew Staugaard, Jr. - 304 pages - Order No. 21798 \$13.95

68000 Microprocessor Handbook

This handbook gives a complete comprehensive picture of the 16 bit 68000 microprocessor, its timing, and special features. Also, several practical application problems and discussed and it is compared to other 16 bit devices. By Adam Osborne - 220 pages. Order No. 411 \$6.99

MC6809 Cookbook

This cookbook explains the basic operation of the 6809 and the 6809E microprocessors. Everything from the timing and clock information to the instruction set are covered. By Carl D. Warren - Order No. 1209 \$6.95

Orders should include title and order no., along with check, m.o., or VISA-Master Card info... Mail to: SS-50 Computing Bookstore, P.O. Box 398, Garland, UT 84312. Include \$1.50 per book for shipping and handling. Please allow for personal checks to clear. Sorry, no COD's. Foreign orders should include \$7.00 per book shipping.

STYLOGRAP real text pr

interactive,

features suc

. CI

• D'

• IN

• P(

• FL

· LI

Versions are a Televideo, Beeh terminals. Nec, 1

OS-9 versions & lowa 50304.

Price

STYLOGRAPHTM is Technical Systems



STYLOGRAPH

6809 WORD PROCESSING SYSTEM

STYLOGRAPH TM (formerly STYLUS) will give your 6809 real text processing muscle. It is a fully integrated, interactive, text processing system with state-of-the-art features such as:

- CURSOR BASED EDITING
- DYNAMIC ON-SCREEN FORMATTING
- INSTANT SCREEN UPDATING
- POWERFUL PRINTING OPTIONS
- SIMPLE, STRAIGHTFORWARD DOCUMENTATION
- FLEX AND OS-9 COMPATIBILITY
- LIBERAL UPDATE POLICY

Versions are available for CT-82, Soroc, Hazeltine, Heath, DEC, Televideo, Beehive, Microterm, Intertube, Lear Siegler, and Gimix 24x80 terminals. Nec, Diablo, Qume, and tty type printers are supported.

OS-9 versions are available from Microware, Box 4865, Des Moines, lowa 50304.

Price: manual only \$15.00 | NY add tty printer \$135.00 | sales other printers \$150.00 | tax

 $\mathbf{STYLOGRAPH}^{\mathsf{TM}}$ is a trademark of \mathbf{SONEX} $\mathbf{SYSTEMS}$. Flex is a trademark of Technical Systems Consultants.



SONEX SYSTEMS

BOX 238 WILLIAMSVILLE, NY 14221

716—634-2466

GIMIX 2MHZ 6809 **PLUS 32K SYSTEM**

IDEAL FOR SOFTWARE DEVELOPMENT

- You can order a system to meet your needs or select the one featured below.
- INCLUDES: 6809 plus CPU #05, Mainframe Cabinet, Mother Board, Power Supply, Fan, 2 Port Serial Card & Cables, 2 Disk Regulator Cards, and 32KB Static Ram. . . \$2194.89
- up to 56K is \$438.14 more.
- 6800 CPU'S AND SYSTEMS ALSO AVAILABLE.

DUAL DRIVE 51/4'' Disk Systems For Use In GIMIX Mainframes.• All Systems Include: Disk Controller, Cable, and GIMIX version of TSC'S Flex.

- Power for the drives is provided by the C.V. power supply in the GIMIX Mainframe and 2 of our disk regulator boards. This gives your disk system the same brownout protection and power supply reliability as the rest of the system.
- When ordered with a **GIMIX** 6809 system, GMXBUG 09 and Boot Prom is also included, or, subject to availability, you may substitute Microware's OS-9 for the GMXBUG/FLEX combination at no charge, or have both, Software Selectable installed on the CPU, for \$150.00 Additional.
- Systems using Uniflex or Video based will also be available.
- Due late 1st quarter of 1981, GIMIX DMA Controller for 5" and 8" drives.


SINGLE DENSITY 2 DRIVE SYSTEM USING OUR **#48 DISK CONTROLLER**

	CAPACITY IN BYTES				
WITH	FORMATTED	UNFORMATTED	PRICE		
2-40 Track (48TPI) Single Sided	199,680	250,000	\$ 998.00		
2-40 Track (48TPI) Double Sided	399,360	500,000	1198.00		
2-80 Track (96TPI) Single Sided	404,480	500,000	1198.00		
2-80 Track (96TPI) Double Sided	808,960	1,000,000	1598.00		

32K STATIC RAM BOARDS

Designed for use with:

★ Existing SS50 Systems * SS50C Extended Address Systems



- Assembled
- Burned In
- Tested

16K...\$328.12 24K . . . \$438.14

32K . . . \$548.15

16K and 24K Versions are socketed for 32K and require only additional 2114's for expansion.

FEATURES:

- Decoding for 4 Extended Address Lines (allows memory decoding up to 1 megabyte)
- . DIP-switch to set extended addressing or disable it
- 4 separate 8K blocks, addressable to any 8K boundary by DIP-switch
- · Each 8K block may be individually disabled
- . Write protect either of two 16K sections
- Low power consumption uses 2114L low power RAMS
- · Fully Socketed
- Gold Bus Connectors
- · Guaranteed 2MHz operation
- To Substitute CMOS RAM, add \$100.00 for 16K, \$150.00 for 24K, \$200.00 for 32K.

TO ORDER BY MAIL

SEND CHECK OR MONEY ORDER OR USE YOUR VISA OR MASTER CHARGE. Please allow 3 weeks for personal checks to clear

U.S. orders add \$5 handling if order is under \$200.00. Foreign orders add \$10 handling if order is under \$200.00.

Foreign orders over \$200.00 will be shipped via Emery Air Frieght COLLECT, and we will charge no handling. Ail orders must be prepaid in U.S. funds. Please note that foreign checks have been taking about 8 weeks for collection so we would advise wiring money, or checks drawn on a bank account in the U.S. Our bank is the Continental Illinois National Bank of Chicago, account #73-32033. Visa or Master Charge also accepted.

GIMIX Inc. reserves the right to change pricing and product specifications at any time without further notice.

GIMIX® and GHOST® are registered trademarks of GIMIX Inc.

Flex and Uniflex are trademarks of Technical Systems Consultants Inc. OS-9 is a trademark of Microware Inc. See their ads for other GIMIX compatible software.

DOUBLE DENSITY 2 DRIVE SYSTEMS USING OUR **#28 DISK CONTROLLER**

	CAPACITY IN BYTES				
WITH	FORMATTED	UNFORMATTED	PRICE		
2-40 Track (48TPI) Single Sided	341,424	500,000	\$1148.00		
2-40 Track (48TPI) Double Sided	718,848	1,000,000	1348.00		
2-80 Track (96TPI) Single Sided	728,064	1,000,000	1348.00		
2-80 Track (96TPI) Double Sided	1,456,128	2,000,000	1748.00		

\$998.19 THE CLASSY CHASSIS

- 25 amp (5V) ferro-resonant constant voltage power supply,
- Heavy weight aluminum cabinet with 3 position key switch, fan, and provisions for two 5" disk drives:
- 6800/6809 Mother Board, fifteen 50 pin and eight DIP-switch addressable 30 pin slots (gold plated pins), fully decoded;
- Baud rate generator on I/O section of Mother Board

- I/O BOARDS for the 30 PIN BUS:

1 Port Serial	. \$	88.41
2 Port RS 232 Serial		128.43
2 Port Parallel		88.42

for the 50 PIN BUS:

8 Port RS 232 Serial	288.40
8 Port RS 232 Serial	318.46
with on board Baud Rate generator. 8 Port Parallel	198 45

FACTORY PRIME STATIC RAMS 2114 Super Low Power 200 ns \$5.90

ADD \$5.00 HANDLING ON ORDERS UNDER \$200.00

Phone, write, or see your dealer for details and prices on our broad range of Boards and Systems for the SS50/SS50C bus and our AC Power Control Products for all computers.



1337 WEST 37th PLACE, CHICAGO, IL 60609 (312) 927-5510 • TWX 910-221-4055